



GOLDER

REPORT

Hydrogeological Investigation

*Shining Hill (Phase 3), 162, 306, 370, 434 & 488 St. John's Sideroad West,
Aurora, Ontario*

Submitted to:

Shining Hill Estates Collection Inc. c/o SCS Consulting Group Ltd.

30 Centurian Drive, Suite 100

Markham, ON,

L3R 8B8

Attention: Ms. Sarah Kurtz, P.Eng.

Submitted by:


Golder Associates Ltd.

100 Scotia Court,

Whitby, Ontario, L1N 8Y6, Canada

20360612 (1000)

March 11, 2021



Distribution List

E-copy - Shining Hill Estates Collection Inc. c/o SCS Consulting Group Ltd.

E-copy - Golder Associates Ltd.

Table of Contents

| | |
|---|-----------|
| 1.0 INTRODUCTION | 1 |
| 2.0 BACKGROUND | 1 |
| 2.1 Site and Project Description | 1 |
| 2.2 Topography and Drainage | 2 |
| 2.3 Physiography and Geology | 3 |
| 2.4 Wellhead Protection Areas (WHPA) | 4 |
| 2.5 Water Well Records | 4 |
| 2.6 Previous Reports | 5 |
| 3.0 SITE CHARACTERIZATION | 5 |
| 3.1 Drilling and Monitoring Well Installation | 5 |
| 3.2 Subsurface Soil Conditions | 6 |
| 3.3 Water Level Monitoring | 6 |
| 3.4 Hydraulic Testing | 7 |
| 3.5 Guelph Permeameter Testing | 8 |
| 3.6 Summary | 10 |
| 4.0 GROUNDWATER CONTROL | 11 |
| 4.1 Temporary Construction Dewatering Permitting | 11 |
| 5.0 HYDROLOGIC WATER BALANCE | 13 |
| 5.1 Methods | 13 |
| 5.1.1 Pre-Development Condition | 14 |
| 5.1.2 Post-Development Condition | 14 |
| 5.2 Water Balance Parameters | 15 |
| 5.3 Water Balance Results | 16 |
| 5.3.1 Pre-Development Condition | 16 |
| 5.3.2 Post-Development Condition | 16 |
| 5.3.3 Post-Development Condition Including Mitigation | 17 |

6.0 DISCUSSION20

7.0 RECOMMENDATIONS23

8.0 CLOSURE23

9.0 REFERENCES25

TABLES

Table 1: Summary of Estimated Hydraulic Conductivity 8

Table 2: Summary of Estimated Infiltration Rates 9

Table 3: Pre-Development Average Annual Water Balance Results 16

Table 4: Post-Development Average Annual Water Balance Results 16

Table 5: Mitigated Post-Development Average Annual Water Balance Results 20

FIGURES

- Figure 1 – Key Plan
- Figure 2A – Site Plan
- Figure 2B – Proposed Development Plan
- Figure 3 – Regulated Areas
- Figure 4 – Wellhead Protection Areas
- Figure 5 – Quaternary Soils Map
- Figure 6 – Ministry Recorded Wells
- Figure 6A – Area Cross-Section A - A’
- Figure 6B – Area Cross-Section B - B’
- Figure 7A – Site Section A - A’
- Figure 7B – Site Section B - B’
- Figure 7C – Site Section C - C’
- Figure 8 – Water Table January 2021

APPENDICES

APPENDIX A

Important Information and Limitations of this Report

APPENDIX B

Supporting Documentation

APPENDIX C

MECP Water Well Records

APPENDIX D

List of Abbreviations and Description of Terms

Record of Borehole Sheets BH101 to BH108 & BH201 to BH206

Plasticity Chart and Grain Size Analysis

(Soil Eng. 2021A and 2021B)

APPENDIX E

Water Level Measurements

APPENDIX F

Hydraulic Conductivity Testing

APPENDIX G

Water Balance Results

1.0 INTRODUCTION

Golder Associates Ltd. (Golder) has been retained by Shining Hill Estates Collection Inc. c/o SCS Consulting Group Ltd. (SCS) to conduct a hydrogeological investigation in support of the draft plan submission process for the proposed residential subdivision development located at 162, 306, 370, 434 & 488 St. John's Sideroad West in Aurora, Ontario (the site), at the location shown on the Key Plan (Figure 1).

The purposes of this hydrogeological investigation are to assess the existing hydrogeological conditions, to prepare a pre- and post-development water budget assessment for the entire site based on current designs, to assess potential low impact development (LID) options and to assess the potential hydrogeological impacts of development. In addition, a preliminary assessment of the need for construction dewatering permitting is included. Based on a meeting with SCS, Beacon Environmental (Beacon) and the Lake Simcoe Region Conservation Authority (LSRCA) on February 3, 2021, it is our understanding that catchment-based water budgets will be required for the off-site willow mineral thicket swamp located southwest of the site and the off-site unevaluated wetland located northeast of the site (discussed in further detail in Section 2.2). As part of the catchment-based water budgets for the willow mineral thicket swamp and the unevaluated wetland, additional instrumentation and water level monitoring will be conducted in these areas, the results of which will be provided in separate reports.

The factual data, interpretations and recommendations contained in this report pertain to a specific project as described in the report and are not applicable to any other project or site location. If the project is modified in concept, location, elevation, or if the project is not initiated within eighteen months of the date of the report, Golder should be given an opportunity to confirm that the recommendations are still valid. In addition, this report should be read in conjunction with the attached "Important Information and Limitations of This Report" which are included in Appendix A. The reader's attention is specifically drawn to this information, as it is essential for the proper use and interpretation of this report.

2.0 BACKGROUND

2.1 Site and Project Description

The site is located at 162 St. John's Sideroad West in Aurora, to the northwest of the intersection of St. John's Sideroad and Yonge Street (see Figure 1 and Figure 2A, Site Plan). The property is currently occupied by a three-storey residence in the northwest portion of the site, a swimming pool, an indoor horse arena with stables, several outdoor horse arenas, a one-storey residence in the southeast corner of the site, and private roadways. A former ice rink was located in the southeast portion of the site. The majority of the site is grass-covered with paved areas adjacent to the three-storey residence, indoor horse arena and former ice rink.

The site is bordered by the Town of Newmarket municipal boundary, an outdoor horse arena and agricultural land to the north, by St. John's Sideroad West and residential homes to the south, by undeveloped lands with light to dense vegetation to the east, and by agricultural land and undeveloped lands with light to dense vegetation to the west.

The Draft Plan of Subdivision prepared by Malone Given Parsons Ltd. (MGP) for the proposed development is provided in Appendix B (MGP, 2021). Based on the Draft Plan of Subdivision, it is understood that the overall development area is approximately 31.8 ha in size and is to be comprised of 88 single-detached homes, a mid/high rise residential building (Block 89), Saint Anne's School (Block 90), a park block (Block 91), a servicing block (Block 93), road widening, internal roads, and a trail head. A natural heritage system / open space block

(i.e., Block 92), approximately 17.7 ha in size, will be located west of the site and is not discussed further in this report.

Based on the Proposed Servicing Plan prepared by SCS (SCS, 2021; see Appendix B), the proposed depths of underground service trenches (e.g., sewers, watermain) range from approximately 2 m to 6.5 m below existing grade. A proposed underground stormwater retention tank is to be located on the east side of the proposed park block, with an invert of 263.22 metres above sea level (masl) and dimensions of about 75 m by 20 m.

A figure showing the Proposed Development Plan is provided as Figure 2B. Details of the proposed development (i.e., building structures, building inverts, etc.) were not available at the time of preparation of this report. However, it is understood that the mid/high rise residential building may include up to two levels of underground parking.

2.2 Topography and Drainage

The site is located within the Tannery Creek sub-watershed of the East Holland River sub-watershed which ultimately reports to Lake Simcoe. Tannery Creek is located at distances ranging from approximately 50 m to 200 m east of the site and has an elevation of approximately 246 masl. Its associated valley lands are generally located adjacent to the eastern limit of the site. A tributary of Tannery Creek (herein referred to as “Tannery Creek West Tributary”) is located approximately 75 m southwest of the site, and has an elevation ranging from approximately 258 masl at St. John’s Sideroad to 270 masl near the western limit of the site. An on-line man-made pond is located approximately 20 m southwest of the site, which discharges to Tannery Creek West Tributary via a riser pipe outlet structure (see Figure 2A). Another tributary of Tannery Creek (herein referred to as “Tannery Creek North Tributary”) is located at distances ranging from approximately 25 m north to 100 m northeast of the site, and has an elevation ranging from approximately 250 masl to 268 masl in the vicinity of the site (refer to Figure 2A).

Based on the Natural Heritage Evaluation prepared by Beacon (Beacon, 2021), it is our understanding that the Tannery Creek North Tributary is a coldwater and intermittent stream. Tannery Creek and the Tannery Creek West Tributary are understood to be coldwater and permanently flowing streams. Downstream of the confluence of the Tannery Creek North Tributary and Tannery Creek, the thermal regime of Tannery Creek is understood to transition to warmwater.

Based on the ecological land classification information (Beacon, 2021; see Appendix B), the site is primarily comprised of anthropogenic land use, mineral cultural meadow, mixed forest, hedgerow and mineral cultural thicket. A mineral meadow marsh (MAM2) is located in a localized low-lying area in the southeast portion of the site. It is noted that this feature will not be retained as part of the development.

The Tannery Creek valley lands located east of the site are primarily comprised of dry-fresh deciduous forest (FOD4), which is not considered to be a groundwater-dependent feature and is therefore not discussed any further.

Southwest of the site, the land surrounding the pond and the Tannery Creek West Tributary is generally comprised of forested areas. Around the perimeter of the pond, Beacon has identified a relatively small forb mineral meadow marsh (MAM2-10), approximately 0.02 ha in size, and a cattail mineral shallow marsh (MAS2-1), approximately 0.03 ha in size. A mineral meadow marsh (MAM2), approximately 0.1 ha in size, is located approximately 15 m east of the pond. A willow mineral thicket swamp (SWT2-2), approximately 0.4 ha in size, is also located southwest of the site further downstream of the pond. As mentioned previously, a catchment-based

water budget will be prepared by Golder for the willow mineral thicket swamp and will be provided in a separate report.

A reed-canary grass mineral meadow marsh (MAM2-2) / cattail mineral shallow marsh (MAS2-1) is located approximately 65 m northeast of the site and is situated primarily on the northern adjoining property on the north side of the Newmarket boundary. It is noted that a separate report will be prepared by Golder for this property, which will include a catchment-based water budget for this feature.

Based on available on-line natural heritage mapping from the Ministry of Natural Resources and Forestry (MNRF; <http://www.gisapplication.lrc.gov.on.ca>), an unevaluated wetland is located south of the site, immediately south of the willow mineral thicket swamp (SWT2-2) mapped by Beacon and adjacent to the Tannery Creek West Tributary (see Figure 2A). The portion of the unevaluated wetland that is situated north of St. John's Sideroad West is approximately 0.1 ha in size and the portion of the wetland located south of St. John's Sideroad West is approximately 1.5 ha in size. Also, MNRF mapping indicates that an unevaluated wetland is located approximately 65 m northeast of the site. This feature is inferred to coincide with the abovementioned reed-canary grass mineral meadow marsh (MAM2-2) / cattail mineral shallow marsh (MAS2-1) mapped by Beacon. As mentioned above, a catchment-based water budget will be prepared for this feature and issued in a separate report to be prepared by Golder.

The site is generally located on tableland areas between Tannery Creek and the north and west tributaries of Tannery Creek, situated at elevations ranging from approximately 266 masl to 272 masl. As indicated on the Existing Storm Drainage Plan prepared by SCS (SCS, 2021; see Appendix B), the site is divided into a total of five catchments, defined as Catchments 101 to 105.

Stormwater runoff in Catchments 101 (4.12 ha in size) and 105 (2.68 ha) generally drain in a south to southwest direction towards the on-site mineral meadow marsh (MAM2), the Tannery Creek West Tributary, the willow mineral thicket swamp (SWT2-2), the off-site mineral meadow marsh (MAM2), the forb mineral meadow marsh (MAM2-10), the cattail mineral shallow marsh (MAS2-1), and the on-line pond. In Catchments 102 (3.62 ha) and 104 (1.06 ha), stormwater runoff generally drains in a northeast direction towards the Tannery Creek North Tributary and the reed-canary grass mineral meadow marsh (MAM2-2) / cattail mineral shallow marsh (MAS2-1). In Catchment 103 (2.39 ha), stormwater runoff generally drains in an east direction towards Tannery Creek.

Available on-line LSRCA mapping (<https://maps.lsrca.on.ca>) indicates that portions of the site are located within LSRCA regulated areas (see Figure 3). Also, based on MNRF mapping, the western portion of the site is located within the Oak Ridges Moraine Conservation Plan Area (Ontario Regulation 140/02) and is part of the Greenbelt, as shown on Figure 3, Regulated Areas.

2.3 Physiography and Geology

The site is mapped within the physiographic region of southern Ontario known as the Schomberg Clay Plains. The physiographic region known as the Oak Ridges Moraine is mapped approximately 700 m west of the site (Chapman and Putnam, 2007). However, as mentioned in Section 2.2, available Region mapping indicates that the western portion of the site is located within the Oak Ridges Moraine Conservation Plan Area (Ontario Regulation 140/02), as shown on Figure 3.

According to published mapping and as presented on Figure 5, Quaternary Soils Map, the surficial soil conditions are composed of fine-textured glaciolacustrine deposits of silt and clay. Off-site to the east and west, the fine-textured glaciolacustrine deposits are overlain by modern alluvial deposits that are mapped parallel to the Tannery

Creek valley lands and the Tannery Creek West Tributary. A flow terrace is mapped to the east of the site, on the west side of the Tannery Creek valley lands.

The geologic mapping is generally consistent with the conditions encountered during the site-specific subsurface investigation conducted by Soil Engineering Ltd. (see Section 3.2), which indicates relatively thin non-cohesive silt and sand deposits underlain by thick silty clay deposits are predominant.

2.4 Wellhead Protection Areas (WHPA)

Available on-line Region of York (Region) mapping (<https://ww6.yorkmaps.ca>) indicates that the site is located within an area designated by the Region as Wellhead Protection Areas WHPA-Q1 and -Q2, where WHPA-Q1 is an area designated as being within the cone of influence of a municipal well and WHPA-Q2 is an area where future reduction in recharge would significantly impact that area. Further with respect to the WHPA-Q1 area, the site is located within areas designated as WHPA-B/C/D areas, or the 2-, 5- and 25-year travel time zones, respectively, as shown on Figure 4, Wellhead Protection Areas.

Two municipal wells (nos. 6918411 and 7285109) are located approximately 600 m east of the site and one municipal well (no. 6916976) is located approximately 1.3 km northeast of the site. It is noted that the site is not located within a Significant Groundwater Recharge Area (SGRA), which is defined by the Region as areas with porous soils such as sand or gravel that have higher than average infiltration rates and that are hydraulically connected to a groundwater supply well. Refer to Section 2.5, Water Well Records, for further discussion on the two municipal supply wells.

2.5 Water Well Records

Water well records were obtained from the Ministry of the Environment, Conservation and Parks (MECP). Approximately 20 water well records were reported within 500 m of the site, three of which are reported to be located on the site (nos. 6901581, 6915585 and 6923894). The locations of the reported water well records are shown on Figure 6, Recorded Wells. A table summarizing the water well record data is provided in Appendix C, MECP Recorded Wells. It is noted that historically there was not a requirement to register dug wells with the MECP, and they can be under-represented in the water well record database.

Little information was provided on one of the records (no. 7326065), which is not discussed further. The remaining 19 wells were constructed between 1949 and 2017 and include six test holes/observation wells and 13 water supply wells. The water supply wells are comprised of:

- Two public use wells (i.e., nos. 6901581 and 6915585) and one domestic well (i.e., no. 6923894) located on the east side of the site, all of which are drilled wells with well depths ranging from 49.7 metres below ground surface (mbgs) to 81.4 mbgs. The three wells were constructed between 1961 and 1997. The status of these wells is not known to Golder, and it is recommended that, if present, they be decommissioned in accordance with applicable legislation as part of site development activities;
- One public use well (i.e., no. 6913488) located approximately 100 m east of the site. This drilled well is situated on the west side of Tannery Creek in the valley lands, with a ground surface elevation of approximately 251.8 masl, and with a reported well depth of 50.3 m; and
- Seven domestic wells, all of which are drilled wells with well depths ranging from about 29.2 mbgs to 116.4 mbgs and two livestock wells, both of which are bored wells with well depths ranging from about 10.1 mbgs to 13.7 mbgs.

Cross sections summarizing the reported soil stratigraphy on the well records are provided on Figures 6A and 6B, MECP Section A - A' and B - B', respectively. In general, the wells were reported to encounter thick clay or till soil units at surface, which contained confined sand or gravel layers/units or were underlain by confined sand or gravel units at various depths. These various confined sand or gravel layers/units are inferred to be the primary aquifers utilized by the private wells. At the three wells present on the site, the reported thickness of the clay/till is on the order of 50 m or more.

Based on the MECP water well record search and our experience in the area, active private well use may be expected generally to the northwest of the intersection of St. John's Sideroad and Yonge Street. The relatively recent subdivision developments located south of St. John's Sideroad and northeast of the intersection of Bathurst Street and St. John's Sideroad West in the Town of Aurora, and about 700 m northeast of the site in the Town of Newmarket are municipally serviced by groundwater-based supplies, although remnant private wells may be present on properties that pre-date the recent developments.

As mentioned in Section 2.4, available on-line Region mapping indicates that two municipal wells (nos. 6918411 and 7285109) are located approximately 600 m east of the site and one municipal well (no. 6916976) is located approximately 1.3 km northeast of the site, as shown on Figures 4 and 6. These municipal wells are screened in a deep confined sand and gravel unit at depths ranging from approximately 97.6 mbgs to 106.7 mbgs and overlain by thick clay/till units.

2.6 Previous Reports

The following geotechnical reports have been prepared for the site by Soil Engineering Ltd. (Soil Eng.) and were provided to Golder:

- Soil Engineering Ltd. (January 2021). *A Geotechnical Investigation And Slope Stability Assessment For Proposed Residential Development, Shining Hill Phase 3, 162 St. John's Sideroad, Town of Aurora.* (Soil Eng., 2021A); and
- Soil Engineering Ltd. (January 2021). *A Geotechnical Investigation For Proposed School Block, Shining Hill Phase 3, 306 St. John's Sideroad, Town of Aurora.* (Soil Eng., 2021B).

The factual subsurface data and information obtained in these geotechnical investigation reports were reviewed and pertinent data was used in preparation of this report. The existing borehole and monitoring well locations from the geotechnical investigation are shown on Figure 2A, and the accompanying Record of Borehole sheets are attached in Appendix D.

3.0 SITE CHARACTERIZATION

3.1 Drilling and Monitoring Well Installation

As reported in the geotechnical investigation reports prepared by Soil Eng. (Soil Eng., 2021A/B), the geotechnical field investigation was carried out in September 2020, during which time fourteen boreholes (designated as BH101 to BH108 and BH201 to BH206) were advanced to depths ranging from approximately 6.6 mbgs to 35.3 mbgs. The borehole locations are shown on Figure 2A. The reader is referred to the geotechnical reports for additional details.

Twelve groundwater monitoring wells were installed by Soil Eng. in selected boreholes to monitor groundwater levels and to facilitate Golder's hydrogeological field program. Single groundwater monitoring wells were installed in BH101 to BH108, BH202 and BH205, and a nested groundwater monitoring well was installed at BH206

located near the on-line pond and the Tannery Creek West Tributary (i.e., BH206-D [deep] and BH206-S [shallow]). The wells consist of 50 mm diameter PVC pipe screens surrounded with filter sand pack and completed with a flush-mount or stick-up monument casings.

In addition, one shallow piezometer (P) and staff gauge (SG) pair, P1/SG1, was manually installed by Golder on November 16, 2020, in the Tannery Creek West Tributary. P1/SG1 is also located within the willow mineral thicket swamp (SWT2-2), as shown on Figure 2A. The shallow piezometer (19 mm inside diameter stainless steel drive point model) was installed to an approximate depth of 1.5 mbgs. The pair was installed to assess the vertical hydraulic gradient at the Tannery Creek West Tributary.

The as-installed piezometer and staff gauge locations and the ground surface and top-of-pipe/gauge elevations were surveyed by Golder using a Trimble Geo 7X GPS capable of 0.1 m accuracy. The ground surface elevations are referenced to geodetic datum.

The subsurface soil and groundwater conditions encountered in the boreholes, and details of the monitoring well installations are provided on the Record of Borehole sheets (Appendix D).

3.2 Subsurface Soil Conditions

A detailed summary of subsurface soil conditions encountered at the borehole locations is provided in Soil Eng.'s geotechnical investigation reports (Soil Eng., 2021A/B), to which the reader is referred. The Record of Borehole sheets, grain size distribution curves and Atterberg limits testing results for selected soil samples are provided in Appendix D.

The surficial materials encountered at the borehole locations generally consist of topsoil, pavement structure, fill materials and surficial deposits of native silt and sand.

The fill or topsoil fill was encountered in all boreholes except for BH102, BH104, BH106 and BH206. The fill consisted predominantly of topsoil and silty sand, with silty clay, sandy silt or silt encountered at some locations. Where encountered, the fill extended to depths ranging between 0.8 mbgs and 3.3 mbgs, with an average thickness of approximately 1.7 m.

The topsoil and fill were generally underlain by a non-cohesive native deposit ranging in gradation from silt to sand, with an average thickness of approximately 3.2 m. The non-cohesive unit was encountered in all boreholes except for BH101 and BH107.

A deposit of silty clay was generally encountered below the non-cohesive unit or below the fill (e.g., in BH101 and BH107), and was encountered in all boreholes except for BH201 and BH202. Where encountered, the silty clay unit extended to the depth of exploration, which ranged from approximately 6.6 mbgs to 35.3 mbgs.

Cross sections summarizing the encountered soil stratigraphy are provided on Figures 7A to 7C, Site Sections A - A', B - B' and C - C', respectively.

3.3 Water Level Monitoring

Groundwater levels were manually measured at the monitoring wells by Soil Eng. on September 29, 2020, and by Golder on November 16, November 24 and December 1, 2020, and January 19, 2021. Water level depths and elevations are provided in Table E-1, Water Level Depths and Elevations (Appendix E). It should be noted that these observations reflect the groundwater conditions encountered at the time of the field investigation and some

seasonal and annual fluctuations should be anticipated. Further, stabilized groundwater conditions may not have been present at BH106 on September 29, November 16, November 24, and December 1, 2020.

The depth to groundwater at the monitoring wells ranged from 1.33 mbgs (BH104 on January 19, 2021) to 4.70 mbgs (BH202 on November 24, 2020) and from elevations of 258.30 masl (BH107 on September 29, 2020) to 271.68 masl (BH206-D [deep] on January 19, 2021) on the dates monitored. The groundwater elevation data on September 29, 2020 are shown on the Record of Borehole Sheets (Appendix D), and the groundwater elevation data on December 1, 2020 and January 19, 2021 are shown on Figures 7A to 7C, Site Sections A - A', B - B' and C - C', respectively. The groundwater elevation data from January 19, 2021 is presented on Figure 8, Water Table (January 2021). In general, shallow groundwater flow is inferred to follow topography, with flow in an eastern direction towards Tannery Creek, in a northeast direction towards the Tannery Creek North Tributary, and in a south to southwest direction towards the Tannery Creek West Tributary and the pond, depending on location (refer to Figure 8).

The groundwater elevations at BH206-D (deep) ranged from about 1.9 m to 2.2 m higher than at BH206-S (shallow) during the monitoring events, indicating an upward vertical gradient at that location. It is noted that the monitoring well in BH105 was installed by Soil Eng. for geotechnical purposes and was screened in the silty clay unit at a lower elevation (i.e., 250.0 masl to 253.1 masl) relative to the other monitoring wells. Therefore, the groundwater levels measured in BH206-D and BH105 are not considered representative of water table conditions.

At staff gauge SG1, located in the Tannery Creek West Tributary, a water depth ranging from 0.26 m to 0.29 m was recorded on the monitoring events on November 16, November 24 and December 1, 2020, and January 19, 2021; flowing water was observed in the Tannery Creek West Tributary on those dates. A downward hydraulic gradient was observed at P1/SG1 on November 16, November 24 and December 1, 2020. An upward hydraulic gradient was observed at P1/SG1 on January 19, 2021. Below grade water levels were recorded at P1 on the monitoring events on November 16, November 24 and December 1, 2020, and January 19, 2021.

Automatic data loggers (i.e., pressure transducers) were installed at BH102, BH107, BH206-D (deep) and BH206-S (shallow) on December 1, 2020, set to record every four hours and downloaded on January 19, 2021. Daily precipitation data was obtained from Environment and Climate Change Canada (ECCC) for the Toronto North York Meteorological Station (ID 615S001), which was the nearest station to the site with daily precipitation data for this period. Hydrographs of the logger data with daily precipitation data are provided as Figures E-2 to E-5, Appendix E. As shown, the data indicate that the groundwater elevation in BH102 and BH107 and increases in delayed response to some rain events during this period. A similar but muted groundwater elevation trend is observed at BH206-D (deep), while a steady groundwater elevation increase was observed at BH206-S (shallow). It is noted that the data loggers will remain in these four monitoring wells until the summer of 2021 (or until construction begins) to monitor seasonal groundwater levels at the site, the results of which will be reported under separate cover.

3.4 Hydraulic Testing

Single well response testing (i.e., rising head tests) was carried out at BH103, BH108 and BH202 on November 16, 2020, and at BH101 and BH206-S (shallow) on December 1, 2020. The rising head tests were carried out by rapidly lowering the water levels by purging with a dedicated Waterra footvalve and tubing. The resulting water level recoveries were monitored with an electronic water level tape and automatic data logger. The recovery data were analyzed using the AQTESOLV for Windows (1996 – 2007) Version 4.5 software. The Bouwer and Rice (1976) method for unconfined conditions was applied to the rising head test data. Estimates of hydraulic

conductivity (K) obtained from the rising head tests are summarized below in Table 1. Summary printouts of the rising head test data and results from AQTESOLV are included in Appendix F.

Table 1: Summary of Estimated Hydraulic Conductivity

| Borehole | Unit Screened | Depth of Monitoring Well (mbgs) | Method | K (cm/s) |
|-------------------|-----------------|---------------------------------|------------------------------------|--------------------|
| BH101 | SILTY CLAY | 7.6 | Bouwer and Rice (1976), unconfined | 2×10^{-6} |
| BH103 | SANDY SILT | 4.6 | Bouwer and Rice (1976), unconfined | 1×10^{-3} |
| BH108 | SANDY SILT | 4.6 | Bouwer and Rice (1976), unconfined | 5×10^{-4} |
| BH202 | SILTY FINE SAND | 6.1 | Bouwer and Rice (1976), unconfined | 4×10^{-4} |
| BH206-S (shallow) | SILTY CLAY | 7.6 | Bouwer and Rice (1976), unconfined | 3×10^{-6} |

Notes:

mbgs – metres below ground surface. cm/s – centimetres per second

The hydraulic conductivity estimates for the non-cohesive sandy silt and silty fine sand soils ranged from 4×10^{-4} cm/s to 1×10^{-3} cm/s, with a geometric mean of 6×10^{-4} cm/s (n=3). The hydraulic conductivity estimates for the silty clay unit ranged from 2×10^{-6} cm/s to 3×10^{-6} cm/s, with a geometric mean of 3×10^{-6} cm/s (n=2). The estimated hydraulic conductivity values are considered reasonable for the units tested.

3.5 Guelph Permeameter Testing

Soil infiltration rate testing was carried out on November 24, 2020 in the unsaturated zone using a Guelph Permeameter (Soilmoisture Equipment Corp., Model 2800K1). The Guelph Permeameter was operated in general accordance with the procedures outlined by the manufacturer (Soilmoisture Equipment Corp., 2012) using a single head method. The apparatus was installed at the base of hand-augered test holes.

Once the outflow of water at the depth of installation reached a steady-state flow rate, the field-saturated hydraulic conductivity, K_{fs} , of the soil was estimated using the following equation (Elrick et. al., 1989):

$$K_{fs} = \frac{C_1 Q_1}{2 \pi H_1^2 + \pi a^2 C_1 + 2 \pi \frac{H_1}{\alpha^*}}$$

Where: C_1 = shape factor
 Q_1 = flow rate (cm³/s)
 H_1 = water column height (cm)
 a = well radius (cm)
 α^* = alpha factor (0.12 cm⁻¹ for Type 3 soils)

The field data and analysis of the infiltration rate tests are presented as Figures F-1 to F-5, Appendix F. Based on the resulting K_{fs} (cm/s), the corresponding infiltration rates (mm/hr) were estimated using the approximate

relationship presented in the *Low Impact Development Stormwater Management Planning and Design Guide* (or “*Design Guide*”) (TRCA and CVCA, 2010). A summary of the infiltration rate test results is presented in Table 2, below.

Table 2: Summary of Estimated Infiltration Rates

| Test | Soil Description | Depth Relative to Grade (mbgs) | Est. Field-Saturated Hydraulic Conductivity K_{fs} (cm/s) | Estimated Infiltration Rate ¹ (mm/hr) | Correction Factor | Corrected Estimated Infiltration Rate ² (mm/hr) |
|---------------------|---|--------------------------------|---|--|-------------------|--|
| GP-101 (near BH101) | Inferred SILTY SAND (FILL) ³ | 1.0 | 9×10^{-5} | 49 | 3.5 | 14 |
| GP-102 (near BH102) | SILT | 0.7 | 1×10^{-5} | 30 | 2.5 ⁵ | 12 |
| GP-105 (near BH105) | SAND | 0.8 | 1×10^{-4} | 50 | 3.5 | 14 |
| GP-106 (near BH106) | Inferred SILTY FINE SAND ⁴ | 1.1 | 3×10^{-4} | 62 | 3.5 | 18 |
| GP-206 (near BH206) | SAND | 0.7 | 1×10^{-3} | 75 | 2.5 ⁵ | 30 |

Notes:

mbgs – metres below ground surface. cm/s - centimetres per second. mm/hr – millimetres per hour

¹ – based on Table C1 from TRCA and CVCA (2010).

² – correction factor in accordance with Table C2 from TRCA and CVCA (2010).

³ – the base of the test hole was near the contact point between silty sand fill and the underlying silty clay unit. In Golder’s opinion, this result is more representative of silty sand fill.

⁴ – the base of the test hole was near the contact point between silty fine sand and the underlying silty clay unit. In Golder’s opinion, this result is more representative of silty fine sand.

⁵ – should the clearance between the invert of the LID feature(s) and the underlying silty clay unit be less than 1.5 m, the correction factor should be increased to 3.5.

The field-saturated hydraulic conductivity values of the silty sand fill, silt, silty fine sand, and sand ranged from approximately 1×10^{-5} cm/s to 1×10^{-3} cm/s, with corresponding infiltration rates ranging from 30 mm/hr to 75 mm/hr.

The infiltration rate estimates from this investigation are based on the test methods discussed above and are for the corresponding fill/soil types encountered. They represent the fill/soil conditions at the tested locations and depths only; conditions may vary between and beyond the tested locations. Care should be taken during construction of any proposed infiltration measures to preserve the existing soil structure and avoid compaction and re-working which could reduce its infiltrative properties.

For preliminary design purposes, a correction factor was applied to estimate the design infiltration rate in accordance with guidance provided in TRCA and CVCA (2010), to account for potential reductions in soil permeability due to compaction, smearing during the construction of a given infiltration feature and the gradual accumulation of fine sediments over the lifespan of the infiltration feature. Based on the guidance, a correction factor of 2.5 to 3.5 was applied to the estimated infiltration rates. The corrected infiltration rate estimate ranges from approximately 12 mm/hr to 30 mm/hr, with a geometric mean of 17 mm/hr (n=5). As noted above in Table 2,

should the clearance between the invert of the LID feature(s) and the underlying silty clay unit be less than 1.5 m, the correction factor should be increased to 3.5 where applicable.

3.6 Summary

The site is currently occupied by a three-storey residence in the northwest portion of the site, a swimming pool, an indoor horse arena with stables, several outdoor horse arenas, a one-storey residence in the southeast corner of the site, and private roadways. The majority of the site is grass-covered with paved areas adjacent to the three-storey residence, indoor horse arena and former ice rink. The site is generally located on tableland areas between Tannery Creek and the North and West Tributaries of Tannery Creek and is divided into a total of five stormwater catchments, defined by SCS as Catchments 101 to 105. Portions of the site are mapped within LSRCA regulated areas, and the western portion of the site is mapped within the Oak Ridges Moraine Conservation Plan Area and Greenbelt.

Based on the results of the subsurface investigation, a non-cohesive deposit ranging in gradation from silt to sand is the predominant surficial native soil type at the site. The non-cohesive deposit had an average thickness of about 3.2 m but was locally absent at two of 14 borehole locations. It was generally overlain by about 0.8 m to 3.3 m of fill, typically comprised of topsoil fill and silty sand fill, except at boreholes BH102, BH104, BH106 and BH206 where the fill was absent. The estimated geometric mean hydraulic conductivity (below the water table) of the surficial non-cohesive sandy silt and silty fine sand soils was 6×10^{-4} cm/s (n=3). The estimated geometric mean design infiltration rate (above the water table) of the silt, silty fine sand, and sand was 17 mm/hr (n=4). A relatively thick deposit of silty clay was encountered below the non-cohesive unit or below the fill (e.g., in BH101 and BH107) in all boreholes except for BH201 and BH202. Where encountered, the silty clay unit extended to the depth of exploration, which ranged from approximately 6.6 mbgs to 35.3 mbgs. On-site water well records indicate the silty clay unit is on the order of 50 m thick. The estimated geometric mean hydraulic conductivity (below the water table) of the silty clay unit was 3×10^{-6} cm/s (n=2).

The depth to groundwater at the monitoring wells ranged from 1.33 mbgs to 4.70 mbgs and from elevations of 258.30 masl to 271.68 masl on five monitoring events between September 2020 and January 2021, although seasonal and annual fluctuations should be expected. In general, shallow groundwater flow is inferred to follow topography, with flow in an eastern direction towards Tannery Creek, in a northeast direction towards the Tannery Creek North Tributary, and in a south to southwest direction towards the Tannery Creek West Tributary and the pond, depending on location.

Off-site to the southwest along the Tannery Creek West Tributary, Beacon has identified a relatively small forb mineral meadow marsh (MAM2-10) and a cattail mineral shallow marsh (MAS2-1) around the perimeter of an on-line pond, an off-site mineral meadow marsh (MAM2) approximately 15 m downstream of the pond, and an off-site willow mineral thicket swamp (SWT2-2) further downstream. During the five monitoring events carried out to date, the vertical hydraulic gradient was upwards at the bi-level monitoring well installed at BH206. This result is consistent with discharging groundwater conditions and information provided by Beacon that the Tannery Creek West Tributary is a permanently flowing coldwater stream, as is Tannery Creek off-site to the east. Piezometer/staff gauge pair P1/SG1 was installed in the Tannery Creek West Tributary and within the willow mineral thicket swamp. A downward hydraulic gradient was observed at P1/SG1 on November 16, November 24 and December 1, 2020, indicating recharging conditions on those dates. An upward hydraulic gradient was observed at P1/SG1 on January 19, 2021. Below grade water levels were recorded at P1 on the monitoring events on November 16, November 24 and December 1, 2020, and January 19, 2021. As mentioned previously, a

catchment-based water budget will be prepared by Golder for the willow mineral thicket swamp and will be provided in a separate report.

Off-site to the northeast, Beacon has identified a reed-canary grass mineral meadow marsh (MAM2-2) / cattail mineral shallow marsh (MAS2-1) situated primarily on the northern adjoining property within the Newmarket municipal boundary. Beacon indicates that the Tannery Creek North Tributary adjacent to the marsh areas is a coldwater and intermittent stream. A separate report will be prepared by Golder for this property, which will include a catchment-based water budget for this feature.

Stormwater runoff in Catchments 101 and 105 generally drain in a south to southwest direction towards the on-site mineral meadow marsh (MAM2), the Tannery Creek West Tributary, the willow mineral thicket swamp (SWT2-2), the off-site mineral meadow marsh (MAM2), the forb mineral meadow marsh (MAM2-10), the cattail mineral shallow marsh (MAS2-1), and the on-line pond. In Catchments 102 and 104, stormwater runoff generally drains in a northeast direction towards the Tannery Creek North Tributary and the reed-canary grass mineral meadow marsh (MAM2-2) / cattail mineral shallow marsh (MAS2-1). In Catchment 103, stormwater runoff generally drains in an east direction towards Tannery Creek.

Most of the infiltration at the site is inferred to discharge locally toward the Tannery Creek North Tributary, the Tannery Creek West Tributary and the Tannery Creek valley lands. A smaller fraction will likely recharge deeper aquifers and result in groundwater base flow further downstream in the East Holland River sub-watershed. The site represents only a portion of the catchment area of these tributaries, and therefore contributes a roughly commensurate portion of the potential groundwater discharge that occurs.

Groundwater use in the area is expected primarily from municipal wells at distances beyond 500 m from the site utilizing a deep confined aquifer (well depths of 97.6 mbgs to 106.7 mbgs). The site is mapped within a Wellhead Protection Area (i.e., within the WHPA-Q1/-Q2 areas, and with respect to the WHPA-Q1, the site is located within the WHPA-B/C/D or the 2-, 5- and 25-year zones, respectively, depending on location). Active private well use within 500 m of the site is generally expected to the northwest of the intersection of St. John's Sideroad and Yonge Street. Thirteen private water supply wells are recorded within 500 m of the site, comprised of two bored wells (depths of 10.1 mbgs and 13.7 mbgs) and 11 deep drilled wells (depths ranging from 29.2 mbgs to 116.4 mbgs), which are inferred to utilize various confined aquifers. Three of the drilled private wells are indicated to be present on the site.

4.0 GROUNDWATER CONTROL

At the time of writing, site designs are at a conceptual or preliminary stage. This section provides a preliminary assessment of short-term (construction) dewatering needs and potential permitting requirements. The assessment can be confirmed once additional details concerning site designs are known. A detailed assessment of construction dewatering needs and potential impacts to receptors should be carried out at the time of detailed design and in conjunction with obtaining dewatering permitting from the MECP.

4.1 Temporary Construction Dewatering Permitting

Based on the Proposed Servicing Plan prepared by SCS (SCS, 2021; see Appendix B), the proposed depths of underground service trenches (e.g., sewers, watermain) range from approximately 2 m to 6.5 m below existing grade. An underground stormwater retention tank is proposed to be located on the east side of the park block, with an invert of 263.22 masl and dimensions of about 75 m by 20 m. Details of the depths and dimensions of the

underground parking structure for the mid/high rise residential building are not currently available. However, it is understood that there may be up to two levels of underground parking provided.

As shown on Table E-1 (Appendix E), groundwater levels across the site were observed to range from approximately 1.3 mbgs to 4.7 mbgs on the dates monitored. In the vicinity of the proposed underground stormwater retention tank, groundwater levels ranged from about 2.3 mbgs to 3.2 mbgs on the dates monitored. In the vicinity of the proposed underground parking structure, groundwater levels ranged from about 2.2 mbgs to 4.2 mbgs on the dates monitored. Seasonal and annual groundwater fluctuations should be anticipated.

With linear servicing ranging from approximately 2 m to 6.5 m below existing grade, the underground stormwater retention tank at a depth of approximately 5 m below existing grade, and the two-level underground parking structure at an assumed depth of 6 m below finished grade (i.e., about 4 m below existing grade), the need for temporary groundwater control during construction is anticipated.

The method of construction dewatering should be solely determined by the Contractor based on their own assessment of the site-specific conditions, and likely by their specialist dewatering contractor. In any case, the groundwater level should be lowered to a minimum of 1 m below the inverts in advance of the excavation reaching the invert levels. Surface water runoff must be directed away from any open excavation.

It is recommended that a licensed, specialist dewatering subcontractor supervise the installation, operation and decommissioning of any dewatering systems for this project, in accordance with applicable legislation. It is understood that a dewatering plan from a specialist subcontractor has not yet been prepared.

Water takings in excess of 50 m³/day are regulated by the MECP. Certain takings of groundwater and storm water for construction site dewatering purposes with a combined total less than 400 m³/day qualify for self-registration on the MECP's Environmental Activity and Sector Registry (EASR). A Category 3 Permit to Take Water (PTTW) is required where the proposed water taking is greater than 400 m³/day. The MECP is currently considering modifications to eligibility criteria for construction water takings under the EASR process where the 400 m³/day water taking limit would only apply to groundwater takings only, with contributions from stormwater no longer included in determining eligibility. At the time of preparation of this report, the MECP is in the process of deliberating any such amendments to eligibility criteria.

The rate of groundwater inflow to excavations will vary during construction. Initially, higher inflow rates will occur as groundwater is removed from storage within the zone of influence. With time, rates will decrease toward a steady-state condition. Incident precipitation into excavations will also need to be managed with the groundwater contributions and, under the current eligibility criteria, must be factored into the total pumping rate.

Groundwater input from the silty clay unit to servicing trenches, the underground stormwater retention tank excavation and the underground parking structure excavation is expected to be negligible, with more significant seepage anticipated from the overlying saturated non-cohesive soils (i.e., silt to sand).

Based on the hydrogeological conditions encountered at the borehole locations, steady state groundwater inflow rates for a typical open length of servicing trench, to the underground stormwater retention tank excavation or to the underground parking structure excavation, may not individually exceed 50 m³/day. However, including the removal of groundwater from storage and the management of incident precipitation from the excavation, and to allow for multiple dewatering activities to proceed simultaneously, the total combined pumping rates are likely to exceed 400 m³/day. Accordingly, the need to obtain a temporary PTTW is conservatively anticipated if all of the construction dewatering occurs simultaneously. In practice, it is likely that the development will be staged, and

construction dewatering will be sequential and not simultaneous. This will likely allow construction dewatering to be carried out under the EASR process, but this assessment will need to be confirmed once additional details are available.

5.0 HYDROLOGIC WATER BALANCE

A water balance assessment for the 14.1 ha site was carried out to assess the potential hydrogeological impacts of the proposed site development with respect to post-development infiltration rates, including potential impacts to groundwater-dependent resources. The assessment included the pre- and post-development conditions within the property boundary, and considered all development proposed for the entirety of the site.

5.1 Methods

The water balance assessment was based on meteorological data obtained from ECCC for the Toronto Buttonville A Meteorological Station (ID 6158409), which was the nearest station to the site with a substantial period of historical data (1986 to 2017), information on current and proposed land uses, and native soil types as identified through the subsurface investigation activities at the site.

Water balance calculations are based on the following equation, which is described in more detail below:

$$P = S + ET + R + I$$

Where: P = precipitation;

S = change in soil water storage;

ET = evapotranspiration;

R = surface runoff; and

I = infiltration (groundwater recharge).

Precipitation data obtained from ECCC for the Toronto Buttonville A station indicate a mean annual precipitation (P) of 864 mm/yr.

Short-term or seasonal changes in soil water storage (S) are anticipated to occur on an annual basis as demonstrated by the typically dry conditions in the summer months and the wet conditions in the winter and spring. Long-term changes (e.g., year to year) in soil water storage are considered to be negligible in this assessment.

Evapotranspiration (ET) refers to water lost to the atmosphere from vegetated surfaces. The term combines evaporation (i.e., water lost from soil or water surfaces) and transpiration (i.e. water lost from plants and trees). Potential ET refers to the loss of water from a vegetated surface to the atmosphere under conditions of an unlimited water supply. The actual rate of ET is typically less than the potential rate under dry conditions (e.g. during the summer months when there is a moisture deficit). The mean annual potential ET for the areas considered in the water balances is approximately 635 mm/yr based on data provided by ECCC.

The mean annual water surplus is the difference between P and the actual ET. The water surplus represents the total amount of water available for either surface runoff (R) or groundwater infiltration (I) on an annual basis. On a monthly basis, surplus water remains after actual evapotranspiration has been removed from the sum of rainfall and snowmelt, and maximum soil or snow pack storage is exceeded. Maximum soil storage is quantified using a water holding capacity (WHC) specific to the soil type and land use. The WHC data obtained from ECCC are shown in Table G-1, Appendix G.

Infiltration rates were estimated using the method presented in the Ontario Ministry of the Environment (MOE) *Stormwater Management Planning and Design (SWM) Manual* (MOE, 2003). There are three main factors that determine the percent infiltration of the water surplus: topography, soil type and ground cover. The sum of the fractions representing these three factors establishes the approximate annual percentage of surplus which can be infiltrated in an area with a sufficient downward groundwater gradient. Wetlands (e.g., the on-site mineral meadow marsh) were assumed to have an upward or negligible downward gradient (i.e., the latter in this instance), resulting in all surpluses being contained in these areas, which were assumed to provide increased evaporation and no infiltration. Pertinent assumptions for pre-development and post-development conditions are described in the following subsections.

5.1.1 Pre-Development Condition

Land use at the site under existing (pre-development) conditions was inferred from details shown on the Topographic Survey (Llyod & Purcell, 2020; see Appendix B) and the ecological land use classification (Beacon, 2021; see Appendix B). The site was considered to be comprised of two sections: the private residential property located west of the hedgerow (Block 90), and the remainder of the private recreational area to the east of the hedgerow. The private residence section includes a three-storey stone residence, a garage, and a courtyard. The private residential property also includes a section of mineral cultural meadow and hedgerow along the north boundary. The south border of the private residential property is situated adjacent to the Tannery Creek West Tributary.

The eastern private recreational area includes an ice rink and a one-storey frame dwelling in the southeast, and an arena / horse stables in the north. The section also includes scattered sections of mineral cultural meadow, mineral cultural thicket, hedgerows, and mixed forest throughout the property, as well as a section of mineral meadow marsh and coniferous plantations towards the south boundary. The surface treatments at both the private residential property and recreational area include gravel, asphalt, and grassed lawns.

5.1.2 Post-Development Condition

Land use at the site under post-development conditions was based on the Draft Plan of Subdivision (see Appendix B). The three-storey stone residence, garage, and adjoining grounds (i.e., Block 90) are proposed to be redeveloped as Saint Anne's School, with no change from the existing land uses. The development on the east side of the site will include single detached houses, a mid/high rise residential development (Block 89) and a neighbourhood park (Block 91). The imperviousness of each land use type was estimated as follows, in accordance with the Proposed Storm Drainage Plan (SCS, 2021; see Appendix B) and information provided to Golder:

- Park: 85% impervious;
- Single detached houses: 59% impervious, of which 25% is paved;
- Mid / High rise residential building: 80% impervious;
- 9.2 m Laneway: 100% impervious;
- 15 m road right of way (ROW): 69% impervious;
- 18 m road right of way (ROW): 78% impervious; and
- 23 m road right of way (ROW): 80% impervious.

5.2 Water Balance Parameters

Based on the results of subsurface investigation activities at the site (see Section 3), the existing surficial soil types (predominantly silt to sand) was considered for the purposes of this report to be silt loam based on the U.S. Bureau of Soils classification system and the relative percentages of sand, silt and clay obtained from selected soil samples. For the purpose of this report, the post-development surficial soil type was also considered to be silt loam, noting that this assumption will need to be confirmed during detailed design on the basis of grading plans and any soil importation requirements. Water holding capacities were assigned to this soil type using the values listed in Table 3.1: Hydrologic Cycle Component Values, from the MOE *SWM Manual* (MOE, 2003), as summarized in Table G-2, Appendix G.

The surplus data obtained from ECCC for the respective water holding capacities were split into infiltration and runoff components by applying an infiltration factor based on Table 3.1 from the MOE *SWM Manual* (MOE, 2003). The infiltration factors were based on a sum of site-specific topography, surficial soil type and vegetative cover factors as presented in Table G-2 of Appendix G. Based on the Topographic Survey (Lloyd and Purcell, 2020; see Appendix B) and the Preliminary Grading Plan (SCS, 2021, see Appendix B), topography factors of 0.1, representing hilly land (with an average slope of 28 m/km to 47 m/km), 0.2, representing rolling land (with an average slope 2.8 m/km to 3.8 m/km), and 0.15, representing land with an average slope between the factors of 0.1 and 0.2 were applied to the pre-development and post-development conditions at the site, where applicable. The silt loam soil was considered to have infiltration properties in between open sandy loam and medium combinations of clay and loam. Therefore, the soil was assigned a soils factor of 0.3. Grass-covered areas, meadows and shrubs were assigned a cover factor of 0.1, representing cultivated land. Forested areas (i.e., thicket, mixed forest, and hedgerow) were assigned a cover factor of 0.2, representing woodland. For impervious surfaces (buildings, gravel, and paved areas), no infiltration factor was applied.

The water balance analysis was developed under the following assumptions:

- WHCs were chosen based on Table 3.1 in the MOE *SWM Manual* (2003) corresponding to the silt loam soil type, existing land uses and proposed post-development conditions.
 - Mineral Cultural Thicket / Mixed Forest / Hedgerow / Plantation (Mature Forest): 400 mm WHC and 0.65 infiltration factor (pre- and post-development conditions).
 - Mineral Cultural Meadow (Pasture and Shrubs): 250 mm WHC and 0.55 infiltration factor (pre- and post-development conditions).
 - Lawn (Urban Lawn): 125 mm WHC and 0.50 or 0.55 infiltration factor, depending on topography (pre- and post-development conditions).
 - Mineral Meadow Marsh: Surplus assumed to equal precipitation minus potential evapotranspiration, with a null (i.e., 0%) infiltration factor.
 - Neighborhood Park (Urban Lawn): 125 mm WHC and 0.60 infiltration factor (post-development).
 - Impervious Areas (i.e., paved parking lots, artificial turf, roads and rooftops): Surplus assumed as 90% of precipitation and null (i.e., 0%) infiltration factor (Conservation Authorities Geoscience Group, 2013).
- Net surplus was estimated by multiplying the estimated monthly surplus (mm/month) for the assumed WHC by the associated drainage area. Annual evapotranspiration and surplus values were obtained from the

meteorological data from the Toronto Buttonville A ECCC Meteorological Station based on the WHC assigned to each land use area.

- Runoff was calculated as the difference between surplus and infiltration.

5.3 Water Balance Results

Average annual water balance assessments were carried out on a site-wide basis as described in Sections 5.1 and 5.2. The results for the pre-development, post-development, and mitigated post-development scenarios are presented in this section.

5.3.1 Pre-Development Condition

Based on the results of the assessment, the average annual pre-development water balance was estimated as summarized in Table 3, and as detailed in Table G-3, Appendix G.

Table 3: Pre-Development Average Annual Water Balance Results

| Component | Average Annual Volume m ³ /yr |
|-------------------------|---|
| | Site-Wide |
| Precipitation (P) | 121,825 |
| Evapotranspiration (ET) | 73,230 |
| Surplus (S) | 48,255 |
| Infiltration (I) | 17,110 |
| Runoff (R) | 31,145 |

For the pre-development condition, the estimated average annual runoff from the site is approximately 31,145 m³ and the average annual infiltration on the site is approximately 17,110 m³.

5.3.2 Post-Development Condition

Based on the results of the assessment, the average annual post-development water balance was estimated as summarized in Table 4, and as detailed in Table G-3, Appendix G.

Table 4: Post-Development Average Annual Water Balance Results

| Component | Average Annual Volume m ³ /yr |
|-------------------------|---|
| | Site-Wide |
| Precipitation (P) | 121,825 |
| Evapotranspiration (ET) | 44,245 |
| Surplus (S) | 77,470 |
| Infiltration (I) | 10,005 |
| Runoff (R) | 67,465 |

For the post-development condition, the estimated average annual runoff from the site is approximately 67,465 m³ and the estimated average annual infiltration on the site is approximately 10,005 m³. As a result of land use changes from site development, runoff is expected to increase by 117% (i.e., 31,145 m³ to 67,465 m³) and infiltration is expected to decrease by 42% (i.e., 17,110 m³ to 10,005 m³) on an average annual basis.

5.3.3 Post-Development Condition Including Mitigation

Average annual infiltration volumes at the site are expected to decrease relative to pre-development conditions and runoff volumes are expected to increase as a result of development. Groundwater recharge from the site is inferred to mainly discharge towards Tannery Creek, the Tannery Creek West Tributary and the Tannery Creek North Tributary valley lands, which are considered to be intermittent and permanent coldwater streams. In addition, the western portion of the site is within the Oak Ridges Moraine Conservation Plan area, and the site is within the WHPA-Q1 (i.e., within the WHPA-B/C/D areas of York Region municipal wells to the east) and WHPA-Q2 areas. Therefore, it is considered prudent to incorporate low impact development (LID) measures into the development design to mitigate against reductions to post-development infiltration rates to the extent practical. Further, the use of LID measures for stormwater runoff from development sites assists to support the natural hydrologic cycle by helping to maintain groundwater recharge, provide additional water quality treatment and reduce the volume of runoff from a site.

The conceptual LID measures proposed for the site as part of the Functional Servicing design by SCS are presented on the LID Plan (SCS, 2021; see Appendix B), and are comprised of catchbasin infiltration trenches, rear-yard infiltration trenches, catchbasin filtration trenches, bioswales, and on-site infiltration as described below. The neighborhood park (Block 91) will also have an underground storm water storage tank that will not impact infiltration or evapotranspiration and will release runoff to the Tannery Creek North Tributary. The designed retention volumes for each of the measures were provided by SCS. The LID measures are located throughout the site so that the enhancements to post-development infiltration rates and the attenuation of storm water volumes will benefit Tannery Creek and the North and West Tributaries of Tannery Creek.

Catchbasin Infiltration Trenches

The Draft Plan of Subdivision (see Appendix B) includes 12 single-detached homes on Street A (Blocks 5-13, 18-20, and 33-34) and 4 on Street C (Blocks 21, 22, 31, and 32). Catchbasin infiltration trenches along the front portion of the proposed single detached units and the adjacent Street A (between Street B and Lane A), including half of the road north of Street B, are proposed to capture flow from roof runoff and other impervious surfaces for these proposed dwellings and road via overland flow.

The catchbasin infiltration trench should be designed in accordance with guidance from the *Low Impact Development Stormwater Management Planning and Design Guide* (TRCA & CVC, 2010). It is understood that the infiltration trench along Street A, adjacent to the Neighbourhood Park above Street B, will be designed to retain up to a 27.3 mm storm event. The infiltration trench south of the Neighbourhood Park along Street A will be designed to retain up to a 9.2 mm storm event. The preliminary infiltration trench designs are shown in the Catchbasin Infiltration Trench Detail in Appendix B (SCS, 2021).

A frequency analysis of precipitation observed at the Toronto Buttonville A station (1986 to 2017) was conducted based on the available storage of the proposed infiltration galleries. Resultant runoff reduction factors of 81% and 57% were applied to the impervious area draining to the infiltration trench north and south of Street B, adjacent to the Neighbourhood Park.

Rear-Yard Infiltration Trenches

The Draft Plan of Subdivision (see Appendix B) includes 9 single detached houses along Street A (Blocks 5-13), 31 along Street B (Blocks 14-17 and 53-79), and 4 along Street C (Blocks 26-29) of the site. Rear-yard infiltration trenches along the proposed single detached units of Street A; adjacent to Tannery Creek, Street B; adjacent to the Tannery Creek West Tributary, and Street C are proposed to capture flow from rear roof runoff for these proposed dwellings via overland flow.

The infiltration trenches should be designed with guidance from the *Low Impact Development Stormwater Management Planning and Design Guide* (TRCA & CVC, 2010). It is understood that the infiltration trenches will be designed to retain up to a 25 mm storm event. The preliminary rear yard infiltration trench design is shown in the Rear Yard Infiltration Trench Detail in Appendix B (SCS, 2021).

A frequency analysis of precipitation observed at the Toronto Buttonville A station (1986 to 2017) was conducted based on the available storage of the proposed infiltration trenches. A resultant runoff reduction factor of 80% was applied to the area draining to the infiltration trenches.

Catchbasin Filtration Trenches

The Draft Plan of Subdivision (see Appendix B) includes 18 single-detached homes along the east side of Street B (Blocks 36-52), 31 along the west and north sides of Street B (Blocks 14-17 and 53-79), 12 on Street C, and 6 on Street A. Catchbasin filtration trenches along the front portion of the proposed single detached units of Streets A, B, and C, the adjacent Street B (18 m ROW), half of the north section of Street B (15 m ROW), and a section of Street A (south of Street B) are proposed to capture flow from both front and full roof runoff and other impervious surfaces for these proposed dwellings and road via overland flow.

The catchbasin filtration trench should be designed in accordance with guidance from the *Low Impact Development Stormwater Management Planning and Design Guide* (TRCA & CVC, 2010). It is understood that the filtration trench will be designed with an impermeable liner, which will promote attenuation and settlement of sediments but will not increase infiltration. The preliminary filtration trench design is shown in the Catchbasin Filtration Trench Detail in Appendix B (SCS, 2021).

Bioswales

The following locations have been identified for the use of bioswales to collect and retain runoff (refer to the Draft Plan of Subdivision; Appendix B):

- Half of the Street A north of Street B is proposed to incorporate a bioswale which will be designed to capture runoff from the street with a design retention of up to a 33.3 mm storm event.
- A portion of Street B adjacent to the Neighbourhood Park is proposed to incorporate a bioswale which will be designed to capture runoff from the street with a design retention of up to a 26.7 mm storm event.
- The front impervious portions of nine lane-access single detached houses along Lane A, including Lane A, will be collected by a bioswale with a design retention of up to a 29.2 mm storm event.

The bioswales should be designed with guidance from the *Low Impact Development Stormwater Management Planning and Design Guide* (TRCA & CVC, 2010). A frequency analysis of precipitation observed at the Toronto Buttonville A station (1986 to 2017) was conducted based on the available storage of the proposed bioswales.

Resultant runoff reduction factors of 82%, 81% and 81% were applied to the areas draining towards Street A, Street B and Lane A, respectively.

On-site Infiltration

The Draft Plan of Subdivision (see Appendix B) includes a neighborhood park (Block 91) to the north, a mid/high rise residential area (Block 89) to the northeast adjacent to Tannery Creek, and a school block for Saint Anne's School (Block 90) to the west adjacent to the Tannery Creek West Tributary. It is anticipated that the school and mid/high rise residential blocks will direct impervious runoff flow to on-site LID features, such as infiltration trenches or bioswales, to achieve 25 mm volume control. The park block will utilize proposed underground storage along the east boundary of the block adjacent to Street A, as shown on the Proposed Servicing Plan (SCS, 2021; see Appendix B). The underground storage measure will provide attenuation to stormwater flows but will not impact infiltration or evapotranspiration. Designs for these LID features are not available at this time but will be demonstrated at the site plan control stage. For the purpose of this assessment, no runoff reduction was considered for these blocks.

Groundwater Elevations

At this time, a conceptual design of the LID measures described above has been completed and details such as final grades and the inverts of LID measures will be available as designs progress. Also, groundwater level monitoring during a time of seasonally high groundwater conditions has not yet been carried out. Groundwater monitoring is on-going and will continue until the summer 2021 (or until construction begins).

The mitigated post-development scenario presented below assumes that a 1 m separation between the subsurface LID inverts and seasonally high groundwater elevations will be maintained. Based on the available data, the depth to groundwater could present challenges to the implementation of subsurface infiltration features used as LID measures. During the September 29, 2020 monitoring event, the average depth to groundwater in the subdivision area (i.e., monitoring wells BH101 to BH104 and BH107 to BH108) was 3.3 m below existing grade. During the January 19, 2021 monitoring event, the average depth to groundwater in the subdivision area (i.e., as above, but including BH106) was 2.2 m below existing grade.

In the event that a 1 m separation distance cannot be maintained, a subsurface LID would still enhance post-development infiltration rates, especially at times of seasonally low groundwater conditions, provided that the outlet or overflow of the LID remains above the seasonally high groundwater level. If the separation distance is less than 1 m, less average annual infiltration and more average annual runoff would be achieved than presented below. In any event, the infiltration features also function to capture and attenuate precipitation events at the site and provide a benefit to the storm water management scheme. The findings presented below should be re-assessed at the time of detailed design and on the basis of seasonal high groundwater elevation data.

Results

Based on the above, the average annual mitigated post-development water balance was estimated as summarized in Table 5, and as detailed in Table G-3, Appendix G.

Table 5: Mitigated Post-Development Average Annual Water Balance Results

| Component | Annual Volume m ³ /yr |
|-------------------------|-------------------------------------|
| | Site-Wide |
| Precipitation (P) | 121,825 |
| Evapotranspiration (ET) | 44,245 |
| Surplus (S) | 77,470 |
| Infiltration (I) | 20,640 |
| Runoff (R) | 56,830 |

The proposed LID mitigation scheme is estimated to increase average annual infiltration by approximately 10,635 m³ and reduce average annual runoff similarly, compared to the un-mitigated post-development condition. As a result, on a site-wide basis, average annual infiltration is estimated to increase by 21% (i.e., 17,110 m³ to 20,640 m³) and average annual runoff is expected to increase by 82% (i.e., 31,145 m³ to 56,830 m³) as a result of development compared to pre-development conditions. As discussed above, if the separation distance between the LID inverts and the seasonally high groundwater elevations is less than 1 m, less average annual infiltration and more average annual runoff would be achieved than presented in Table 5.

6.0 DISCUSSION

The site is generally located on tableland areas between Tannery Creek and the North and West Tributaries of Tannery Creek. Portions of the site are mapped within LSRCA regulated areas, and the western portion of the site is mapped within the Oak Ridges Moraine Conservation Plan Area and Greenbelt.

The findings of the subsurface investigation indicate that shallow native soils at the site are predominantly comprised of a non-cohesive deposit (ranging in gradation from silt to sand) with an average thickness of about 3.2 m and with moderate hydraulic conductivity. The thick underlying deposit of silty clay has moderate to low hydraulic conductivity. Based on MECP water well records, the thickness of the clay/till aquitard at the site is on the order of 50 m or more. Shallow groundwater flow is inferred to follow topography, with flow in an eastern direction towards Tannery Creek, in a northeast direction towards the Tannery Creek North Tributary, and in a south to southwest direction towards the Tannery Creek West Tributary and the man-made on-line pond, depending on location. The on-line pond discharges to the Tannery Creek West Tributary.

A bi-level groundwater monitoring well was installed at BH206 near the on-line pond and the Tannery Creek West Tributary. During the five monitoring events carried out to date, the vertical hydraulic gradient was upwards. This result is consistent with discharging groundwater conditions and information provided by Beacon that the Tannery Creek West Tributary is a permanently flowing coldwater stream, as is Tannery Creek off-site to the east.

Piezometer/staff gauge pair P1/SG1 was installed in the Tannery Creek West Tributary and within the willow mineral thicket swamp. A downward hydraulic gradient was observed at P1/SG1 on November 16, November 24 and December 1, 2020, indicating recharging conditions on those dates. An upward hydraulic gradient was observed at P1/SG1 on January 19, 2021, indicating discharging conditions. Below grade water levels were

recorded at P1 on all monitoring events. As mentioned previously, a catchment-based water budget will be prepared by Golder for the willow mineral thicket swamp in a separate report.

Off-site to the northeast, Beacon has identified a reed-canary grass mineral meadow marsh (MAM2-2) / cattail mineral shallow marsh (MAS2-1) situated primarily on the northern adjoining property within the Newmarket municipal boundary. Beacon indicates that the Tannery Creek North Tributary, located adjacent to the marsh, is a coldwater and intermittent stream. A separate report will be prepared by Golder for this property, which will include a catchment-based water budget for this feature.

The proposed site development is understood to be comprised of 88 single-detached homes, a mid/high rise residential building (Block 89), Saint Anne's School (Block 90), a park block (Block 91), a servicing block (Block 93), road widening, internal roads, and a trail head.

Site designs are at a conceptual or preliminary stage, and therefore a preliminary assessment of short-term (construction) dewatering needs and permitting requirements is provided at this time. The need for temporary construction dewatering during the construction of linear underground site services, an underground stormwater retention tank and the multi-level underground parking structure is expected. The need to obtain a temporary PTTW is conservatively anticipated if all of the construction dewatering activity occurs simultaneously. In practice, it is likely that the development will be staged, and construction dewatering will be sequential and not simultaneous. This will likely allow construction dewatering to be carried out under the EASR process, but this assessment will need to be confirmed once additional details are available. A detailed assessment of potential impacts to receptors should be carried out at the time of detailed design and in conjunction with obtaining dewatering permitting from the MECP.

Site-wide water balance estimates were carried out to assess the potential hydrogeological impacts of the proposed development with respect to average annual post-development infiltration rates. The development of the 14.1 ha site, without the implementation of mitigation measures, is expected to result in a 42% reduction in average annual infiltration.

The proposed LID strategy includes the following measures to enhance post-development infiltration rates:

- catchbasin infiltration trenches that will receive runoff from the front roofs of 12 single-detached homes on Street A and 4 on Street C as well as drainage from the adjacent section of Street A (area between Street B and Lane A), half of the Street A (north of Street B), and other impervious areas.
- rear-yard infiltration trenches: the runoff from the rear roofs of 9 single detached houses along Street A will be directed to a rear-yard infiltration trench adjacent to Tannery Creek; the runoff from the rear roofs of 31 single detached houses along Street B will be directed to a rear-yard infiltration trench adjacent to the Tannery Creek West Tributary; and, the runoff from the rear roofs of 4 single detached houses along Street C will be directed to a rear-yard infiltration trench.
- the runoff from the front roofs of 9 lane-access single detached houses on Lane A as well as the drainage from Lane A, half of Street A (north of Street B), and north half of Street B (adjacent to Neighbourhood Park) will be directed to three separate bioswales.

It is also expected that additional LID features to enhance post-development infiltration rates will be implemented for Saint Anne's School (Block 90) and the mid/high rise residential block (Block 89) that were not included in this assessment.

Other LID measures are proposed that will promote storm water attenuation and settlement of sediments but will not increase infiltration. The neighborhood park (Block 91) will have an underground storm water storage tank that will not impact infiltration or evapotranspiration and will release runoff to the Tannery Creek North Tributary. Catchbasin filtration trenches with an impermeable liner along the front portion of the proposed single detached units of Streets A, B, and C, the adjacent Street B (18 m ROW), half of the north section of Street B (15 m ROW), and a section of Street A (south of Street B) are proposed to capture flow from both front and full roof runoff and other impervious surfaces for these proposed dwellings and road via overland flow.

In the mitigated post-development scenario, average annual infiltration is estimated to increase by approximately 21% (i.e., 17,110 m³ to 20,640 m³) and average annual runoff is estimated to increase by approximately 82% (i.e., 31,145 m³ to 56,830 m³), relative to pre-development rates. It is recommended that the LID measures be designed to target a mitigated post-development infiltration rate within 10% of pre-development rates. However, as discussed in Section 5.3.3, if the separation distance between the LID inverts and the seasonally high groundwater elevations is less than 1 m, less average annual infiltration would be achieved than presented above. It is therefore recommended that these findings be re-assessed at the time of detailed design and on the basis of seasonal high groundwater elevation data.

The site is expected to contribute a portion of the potential groundwater discharge that occurs to the Tannery Creek North Tributary, the Tannery Creek West Tributary and the Tannery Creek valley lands proportional to its size within the catchment areas of these features, with a smaller fraction likely recharging deeper aquifers resulting in groundwater base flow further downstream in the East Holland River sub-watershed. Based on the above assessment, no reduction in post-development infiltration rates is anticipated and therefore no reduction in baseflow contributions from the site to these watercourses is anticipated.

Two municipal groundwater supply wells are located approximately 600 m east of the site and one municipal well is located approximately 1.3 km northeast of the site. The site is located within the WHPA-Q1 (i.e., within the WHPA B/C/D or the 2-, 5- and 25-year travel time zones, respectively) and the WHPA-Q2 areas. According to Region mapping, the site is not located within a SGRA. Given that no reduction in post-development infiltration rates is estimated at this time, no water quantity reduction to the municipal wells is anticipated. Further, these three municipal wells are screened in a deep confined sand and gravel unit at depths ranging from approximately 97.6 mbgs to 106.7 mbgs, and therefore recharge to this aquifer is expected to occur from a broad lateral extent outside of the WHPA-Q1 area.

Based on the MECP water well record search and our experience in the area, active private well use within 500 m of the site is generally expected to the northwest of the intersection of St. John's Sideroad and Yonge Street. Three private wells are reported to be present on the site that, if present, are recommended to be decommissioned as part of site development activities. Ten other private water well records are reported within 500 m of the site. Given that no reduction in post-development infiltration rates is estimated at this time, no water quantity reduction to any remaining off-site private wells is anticipated.

Given the proposed LID strategy described above, precipitation falling on certain roof and paved areas will be directed to infiltration trenches, catchbasin infiltration systems and bioswales for infiltration. Other areas will infiltrate to grassed areas. The infiltration of runoff from residential roof areas is considered have a low potential to degrade groundwater quality. Runoff from paved areas such as low traffic roads, parking areas and sidewalks typically has increased concentrations of one or more of metals, oil and grease, and road salt and should be pre-treated to remove large and fine particulate from runoff using devices such as oil and grit separators, or sedimentation chambers or sumps. With properly designed pre-treatment for paved areas, this infiltration is

expected to be moderately clean and is expected to have a low potential to degrade groundwater quality at the site, noting that, with the exception of road salt, these materials quickly become immobile in the shallow subsurface. Given the presence of a shallow groundwater flow regime, where most infiltration at the site is expected to report to Tannery Creek and the North and West Tributaries of Tannery Creek, the potential for water quality impacts to off-site private and municipal water wells using primarily deep confined aquifers is considered to be low.

7.0 RECOMMENDATIONS

Based on the findings of this hydrogeological investigation, the following are recommended:

- The monitoring well network should be maintained and used for further monitoring of groundwater levels. It is understood that data loggers will remain in BH102, BH107, BH206-D (deep) and BH206-S (shallow) and additional manual groundwater level monitoring will occur until the summer of 2021 (or until construction begins) to monitor seasonal groundwater levels at the site. Once the monitoring wells are no longer required, decommissioning should occur in accordance with applicable legislation.
- A detailed assessment of construction dewatering needs and potential impacts to receptors should be carried out at the time of detailed design and in conjunction with obtaining dewatering permitting from the MECF. In this regard, a door-to-door private well survey can be carried out to identify any groundwater users within the zone of influence, if required.
- It is recommended that the LID measures be designed to target a mitigated post-development infiltration rate within 10% of pre-development rates. If the separation distance between the LID inverts and the seasonally high groundwater elevations is less than the 1 m assumed in this assessment, less average annual infiltration would be achieved than presented herein. It is therefore recommended that these findings be re-assessed at the time of detailed design and on the basis of seasonal high groundwater elevation data.
- Other LID measures to promote infiltration should be investigated at the time of detailed design for the areas currently designated as On-Site Infiltration in the LID Plan.
- The presence of any private water wells on the site should be investigated. All existing private water wells should be decommissioned in accordance with applicable legislation as part of site development activities.

8.0 CLOSURE

We trust that this submission meets your current requirements. If you have any questions regarding the contents of this report, please contact the undersigned.

Signature Page

Yours truly,

Golder Associates Ltd.



Joel Gopaul, B.A.Sc.
Geo-Environmental Consultant



The seal is circular with the text "LICENSED PROFESSIONAL ENGINEER" at the top and "PROVINCE OF ONTARIO" at the bottom. Inside the seal, it reads "D. P. HINTON" and "101226302".

David Hinton, P.Eng.
Surface Water Engineer



The seal is circular with the text "PROFESSIONAL GEOSCIENTIST" at the top and "ONTARIO" at the bottom. Inside the seal, it reads "CHRISTOPHER M. KOZUSKANICH" and "PRACTISING MEMBER 0315".

Chris Kozuskanich, P.Geo.
Associate, Senior Hydrogeologist

JJG/MR/DH/MK/CMK/lb


Golder and the G logo are trademarks of Golder Associates Corporation

[https://golderassociates.sharepoint.com/sites/133588/project files/6 deliverables/20360612 \(1000\) rep 2021'03'11 hydrogeological investigation - shining hill \(phase 3\), 162, 306, 370, 434 & 488 st. john's sideroad west \(rev0\).docx](https://golderassociates.sharepoint.com/sites/133588/project%20files/6%20deliverables/20360612%20(1000)%20rep%202021%2003%2711%20hydrogeological%20investigation%20-%20shining%20hill%20(phase%203),%20162,%20306,%20370,%20434%20&%20488%20st.%20john%27s%20sideroad%20west%20(rev0).docx)

9.0 REFERENCES

- Beacon Environmental. (March 2021). Draft Natural Heritage Evaluation, Shining Hill Lands, City of Aurora. (Beacon, 2021).
- Bouwer, H. and R. C. Rice. (1976). A slug test method for determining hydraulic conductivity of unconfined aquifers with completely or partially penetrating wells. *Water Resources Research*, 12 (3): 423-428.
- Chapman, L.J. and Putnam, D.F. (2007). Physiography of southern Ontario; Ontario Geological Survey, Miscellaneous Release--Data 228.
- Conservation Authorities Geoscience Group. (2013). Conservation Authority Guidelines for Development Applications – Hydrogeological Assessment Submissions.
- Elrick, D. E., Reynolds, W. D., and Tan, K. A. (1989). Hydraulic conductivity measurements in the unsaturated zone using improved well analyses. *Ground Water Monitoring*. 9:184-193.
- Lake Simcoe Region Conservation Authority (LSRCA). (2010). East Holland River Subwatershed Plan. (LSRCA, 2010).
- Lake Simcoe Region Conservation Authority (LSRCA) Mapping. (2021). Accessed on-line at <https://maps.lsrca.on.ca/EH5Viewer/index.html?viewer=LSRCARegulations>.
- Ontario Geological Survey. (2010). Surficial geology of Southern Ontario, Ontario Geological Survey, Miscellaneous Release--Data 128-REV.
- Ontario Ministry of the Environment (MOE). (2003). Stormwater Management Planning and Design (SWM) Manual. Queen's Printer for Ontario, ISBN 0-7794-2969-9.
- Ontario Ministry of Natural Resources and Forestry. (2021). Ontario Flow Assessment Tool. Accessed on-line at <https://www.ontario.ca/page/watershed-flow-assessment-tool>.
- Ministry of Natural Resources and Forestry Mapping. (2021). Accessed on-line at <https://www.gisapplication.lrc.gov.on.ca>.
- Malone Given Parsons Ltd. (March 2, 2021). Draft Plan of Subdivision, Part of Lot 86, Concession 1, Town of Aurora, Regional Municipality of York. (MGP, 2021).
- The Region of York Mapping. (2021). Accessed on-line at <https://ww6.yorkmaps.ca>.
- SCS Consulting Group Ltd. (March 2021). Shining Hill Estates Collection Inc., Functional Servicing and Stormwater Management Report: Shining Hill Estates Phase 3 (Aurora). (SCS, 2021).
- Soil Engineering Ltd. (January 2021). A Geotechnical Investigation And Slope Stability Assessment For Proposed Residential Development, Shining Hill Phase 3, 162 St. John's Sideroad, Town of Aurora. (Soil Eng., 2021A).
- Soil Engineering Ltd. (January 2021). A Geotechnical Investigation For Proposed School Block, Shining Hill Phase 3, 306 St. John's Sideroad, Town of Aurora. (Soil Eng., 2021B).
- Soilmoisture Equipment Corp., 2012. Guelph Permeameter 2800 Operating Instructions Manual, Version 0898-2800K1.
- Toronto Region Conservation Authority and Credit Valley Conservation Area (TRCA and CVCA). (2010). Low Impact Development Stormwater Management Planning and Design Guide, Version 1.0.

FIGURES



LEGEND

- - - - - PHASE 3 (AURORA) SITE BOUNDARY

REFERENCES AND NOTES

1. Worldwide Street Maps; Compilation of ESRI & Geographic Partners
2. Malone Given Parson, Draft Plan of Subdivision 16th February 2021



CLIENT
SHINING HILL ESTATES COLLECTION INC.
 C/O SCS CONSULTING GROUP LTD.

PROJECT
HYDROGEOLOGICAL INVESTIGATION
SHINING HILL (PHASE 3)
 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA

CONSULTANT

YYYY-MM-DD 2021-03-09

DESIGNED

PREPARED JPR

REVIEWED JG

APPROVED CMK



TITLE

KEY PLAN


PROJECT NO.
 20360612

CONTROL
 0001

REV.

FIGURE
1

Path: \\golder\gis\complectan\diffcomplectan\clients\Shining_Hill_Estates_Aurora\102_SJ_Johns_Sideroad\20360612_SCS\40_PROD\0001-Hydro\01 | File Name: 20360612_0001-CH-0002.dwg | Last Edited By: Jregier | Date: 2021-03-11 | Time: 4:37:50 PM | Printed By: Jregier | Date: 2021-03-12 | Time: 10:27:25 AM



LEGEND

- - - PHASE 3 (AURORA) SITE BOUNDARY
- SOIL ENG MONITORING WELL
- SOIL ENG BOREHOLE
- GOLDRER PIEZOMETER / STAFF GAUGE
- LINE OF SECTION
- ▲▲▲ UNEVALUATED WETLAND (MNRF)
- ▲▲▲ MAPPED WETLAND (BEACON)
- SITE CONTOURS (1 masl INTERVAL)

REFERENCES AND NOTES

1. MAPPING BASED ON ESRI GEOGRAPHY NETWORK OBM FEATURES AND CLIENT CAD COMPILATIONS
2. WETLAND AND ECOLOGICAL FEATURES, BEACON, FEBRUARY 2021
3. MAPPED FEATURES AND LOCATIONS ARE APPROXIMATE AND NOT TO SCALE

CLIENT
SHINING HILL ESTATES COLLECTION INC.
 C/O SCS CONSULTING GROUP LTD.


| CONSULTANT | YYYY-MM-DD | 2021-03-09 |
|------------|------------|------------|
| DESIGNED | | |
| PREPARED | JPR | |
| REVIEWED | JG | |
| APPROVED | CMK | |

PROJECT
HYDROGEOLOGICAL INVESTIGATION
 SHINING HILL (PHASE 3)
 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA

| TITLE | | PROJECT NO. | CONTROL | REV. | FIGURE |
|------------------|--|-------------|---------|------|-----------|
| SITE PLAN | | 20360612 | 0001 | --- | 2A |

25 mm IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A3/B

Path: \\golder-gsk\workspace\data\diff\mst\shininghill\shining_hill_estates_aurora\162_306_370_434_488_st_johns_sideroad_west\162_306_370_434_488_st_johns_sideroad_west.dwg | File Name: 20360612_001_C14-003.dwg | Last Edited By: jregier Date: 2021-03-05 Time: 3:47:47 PM | Printed By: jregier Date: 2021-03-09 Time: 3:57:14 PM



LEGEND

- PHASE 3 (AURORA) LIMITS
- MAPPED WETLANDS (BEACON)
- LSRCA REGULATED AREA (see note)
- OAK RIDGES MORaine LIMIT (GREENBELT)

- REFERENCES AND NOTES**
1. Mapping based on ESRI Geography Network OBM Features and Client CAD Compilations
 2. Regulated Areas, Lake Simcoe Region Conservation Authority
 3. Mapped Features and Locations are Approximate and Not to Scale



CLIENT
 SHINING HILL ESTATES COLLECTION INC.
 C/O SCS CONSULTING GROUP LTD.

PROJECT
 HYDROGEOLOGICAL INVESTIGATION
 SHINING HILL (PHASE 3)
 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA


TITLE
REGULATED AREAS

| | | |
|-------------------|------------|------------|
| CONSULTANT | YYYY-MM-DD | 2021-03-09 |
| | DESIGNED | |
| | PREPARED | JPR |
| | REVIEWED | JG |
| | APPROVED | CMK |

PROJECT NO. 20360612 **CONTROL** 0001 **REV.** ---- **FIGURE** 3

IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A4 (210 x 297 mm) TO A3 (297 x 420 mm)

Path: \\golder-gsk.com\kadeba\diff\miesasug\m\clients\Shining_Hill_Estates_Aurora\162_St_Johns_Sideroad\PROJ\20360612_SCS\40_PROJ\20360612\001-CH-004.dwg | Last Edited By: jregier Date: 2021-03-05 Time: 4:23:28 PM | Printed By: jregier Date: 2021-03-09 Time: 2:58:41 PM



LEGEND

| | |
|--|--------------------------------|
| | PHASE 3 (AURORA) SITE BOUNDARY |
| | MUNICIPAL SUPPLY WELL |
| | 100 m WHPA A |
| | 2 YEAR WHPA ZONE |
| | 5 YEAR WHPA ZONE |
| | 25 YEAR WHPA ZONE |

- REFERENCES AND NOTES**
1. Mapping based on ESRI Geography Network OBM Features and Client CAD Compilations
 2. Selected MOE Centroid Well Locations have been relocated based on Drillers Record
 3. Region of York, Source Water Protection
 4. Mapped Features and Locations are Approximate and Not to Scale



CLIENT
SHINING HILL ESTATES COLLECTION INC.
C/O SCS CONSULTING GROUP LTD.

PROJECT
HYDROGEOLOGICAL INVESTIGATION
SHINING HILL (PHASE 3)
162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA

TITLE
WELLHEAD PROTECTION AREAS


| | | |
|-------------------|------------|------------|
| CONSULTANT | YYYY-MM-DD | 2021-03-09 |
| DESIGNED | | |
| PREPARED | JPR | |
| REVIEWED | JG | |
| APPROVED | CMK | |

PROJECT NO. 20360612 **CONTROL** 0001 **REV.** ---- **FIGURE** 4



IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A4/B5 TO A3/B4

Path: \\golder-gsk.com\pks\data\diff\m\shining\shining_hill_estates_aurora\162_370_434_488_st_johns_sideroad_west\hydro\GIS - File Name: 20360612_2001-CH-0005.dwg | Last Edited By: jregier | Date: 2021-03-09 | Time: 4:23:15 PM | Printed By: jregier | Date: 2021-03-09 | Time: 3:01:44 PM




LEGEND

- PHASE 3 (AURORA) BOUNDARY
- 19 FLUVIAL SILT, SAND, GRAVEL
- 9b GLACIOLACUSTRINE SAND DEPOSITS
- 9c GLACIOLACUSTRINE SILT & SAND DEPOSITS
- 8a GLACIOLACUSTRINE DEEP WATER DEPOSITS
- 6 ICE CONTACT SEDIMENTS, ESKERS
- 5b ABLATION TILL
- FLOW TERRACE

REFERENCES AND NOTES

1. Mapping based on ESRI Geography Network OBM Features and Client CAD Compilations
2. Quaternary Geology, OGS / GSC Digital Compilation, Queen's Printer



CLIENT
 SHINING HILL ESTATES COLLECTION INC.
 C/O SCS CONSULTING GROUP LTD.

PROJECT
 HYDROGEOLOGICAL INVESTIGATION
 SHINING HILL (PHASE 3)
 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA


TITLE
QUATERNARY SOILS MAP

| | | |
|------------|------------|------------|
| CONSULTANT | YYYY-MM-DD | 2021-03-09 |
| DESIGNED | | |
| PREPARED | JPR | |
| REVIEWED | JG | |
| APPROVED | CMK | |

PROJECT NO. 20360612 CONTROL 0001 REV. --- FIGURE 5

IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A4S1B 28 mm

Path: \\golder-gsk\proj\20360612\GIS\Map_Series_Aurora\162_St_Johns_Sideroad_West\Hydro\G... | File Name: 20360612_2001-CH-0006.dwg | Last Edited By: jregier | Date: 2021-03-05 | Time: 4:14:47 PM | Printed By: jregier | Date: 2021-03-09 | Time: 3:04:23 PM



LEGEND

--- PHASE 3 (AURORA) SITE BOUNDARY

| MOE WATER WELL RECORD | | OAK RIDGES MORAINÉ DATABASE | |
|---------------------------------------|--------------------------|---------------------------------------|----------------------|
| + | TEST OR OBSERVATION WELL | + | OGS / GSC BOREHOLE |
| ○ | DUG WELL | + | MONITORING WELL |
| ● | BORED WELL | ○ | TEST HOLE TO BEDROCK |
| ⊙ | DRILLED WELL | | |
| ⊕ | DRILLED TO BEDROCK | | |
| ○ | MUNICIPAL SUPPLY WELL | | |
| 6200000 | MOE NUMBER | | |

REFERENCES AND NOTES

1. Mapping based on ESRI Geography Network OBM Features and Client CAD Compilations
2. Selected MOE Centroid Well Locations have been relocated based on Drillers Record
3. Abandoned wells, Centroid located wells, and Temporary Shallow Dewatering wells excluded
4. Mapped Features and Locations are Approximate and Not to Scale
5. Ministry Water Well Records, Queen's Printer 2020
6. Conservation Authorities Oak Ridges Moraine (ORM) Coalition / TRCA Database

0 200 400 600 m
1:10000

CLIENT
 SHINING HILL ESTATES COLLECTION INC.
 C/O SCS CONSULTING GROUP LTD.





PROJECT
 HYDROGEOLOGICAL INVESTIGATION
 SHINING HILL (PHASE 3)
 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA

TITLE
MINISTRY RECORDED WELLS

| | | |
|------------|------------|------------|
| CONSULTANT | YYYY-MM-DD | 2021-03-09 |
| DESIGNED | | |
| PREPARED | JPR | |
| REVIEWED | JG | |
| APPROVED | CMK | |

IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A4/B5

Path: \\golder.com\projects\shining_hill\shining_hill\Estates_Aurora\102_S1_Johns_SideRoad\99_PROJ\20360612_SCS\10_PROJ\0001-Hydro\01 | File Name: 20360612_SCS\10_PROJ\0001-Hydro\01 | Last Edited By: jingler Date: 2021-03-05 Time: 3:38:20 PM | Printed By: jingler Date: 2021-03-09 Time: 2:54:44 PM




| | | |
|------------|---|------------|
| CLIENT | SHINING HILL ESTATES COLLECTION INC. C/O SCS CONSULTING GROUP LTD. | |
| CONSULTANT | YYYY-MM-DD | 2021-03-09 |
| | DESIGNED | |
| | PREPARED | JPR |
| | REVIEWED | JG |
| | APPROVED | CMK |

| | | | |
|-------------|--|------|--------|
| PROJECT | HYDROGEOLOGICAL INVESTIGATION SHINING HILL (PHASE 3) 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA | | |
| TITLE | SITE SECTION A - A' | | |
| PROJECT NO. | CONTROL | REV. | FIGURE |
| 20360612 | 0001 | ---- | 7A |

25 mm IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A4/B

Path: \\golder.com\projects\20360612\20360612_SCS\100_PROD\0001-Hydro\01 | File Name: 20360612_001-CH-002.dwg | Last Edited By: jingler | Date: 2021-03-09 | Time: 3:38:20 PM | Printed By: jingler | Date: 2021-03-09 | Time: 3:55:44 PM



| SOILS LEGEND | | |
|--------------|-------------------------------|--|
| | EARTH / TOPSOIL FILL | |
| | GRANULAR FILL | |
| | SAND | |
| | SAND TRACE SILT | |
| | SILTY SAND | |
| | TOPSOIL | |
| | SILTY SAND TRACE CLAY | |
| | SANDY SILT WITH TO TRACE CLAY | |
| | SILTY CLAY | |
| | SILTY SAND DIAMICT | |
| | SILTY CLAY DIAMICT | |

| SECTION LEGEND | | |
|----------------|---|-------------|
| | BH1 | BOREHOLE ID |
| | RECORDED STATIC WATER LEVEL 1st DECEMBER 2020 | |
| | RECORDED STATIC WATER LEVEL JANUARY 2020 | |
| | SCREEN | |


BOUNDARIES BETWEEN SOIL STRATA HAVE BEEN DETERMINED ONLY AT WELL AND TEST WELL LOCATIONS. BETWEEN THE WELLS AND TEST WELLS, BOUNDARIES ARE NOT PROVEN BUT ARE ASSUMED FROM GEOLOGICAL EVIDENCE.

| | | |
|------------|---|------------|
| CLIENT | SHINING HILL ESTATES COLLECTION INC. C/O SCS CONSULTING GROUP LTD. | |
| CONSULTANT | YYYY-MM-DD | 2021-03-09 |
| | DESIGNED | |
| | PREPARED | JPR |
| | REVIEWED | JG |
| | APPROVED | CMK |

| | | | |
|-------------|--|------|--------|
| PROJECT | HYDROGEOLOGICAL INVESTIGATION SHINING HILL (PHASE 3) 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA | | |
| TITLE | SITE SECTION C - C' | | |
| PROJECT NO. | CONTROL | REV. | FIGURE |
| 20360612 | 0001 | ---- | 7C |

IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A4/B

Path: \\golder.com\publicdata\diffusion\shininghill\Clients\Shining_Hill_Estates_Aurora\162_SJ_Links_SitePlan\162_SJ_SCS\162_SJ_SCS\162_SJ_SCS.dwg | File Name: 20360612_2001-CH-002.dwg | Last Edited By: jregier | Date: 2021-03-09 | Time: 3:38:20 PM | Printed By: jregier | Date: 2021-03-09 | Time: 3:50:16 PM



LEGEND

- - - - - PHASE 3 (AURORA) BOUNDARY
- SOIL ENG MONITORING WELL
- SOIL ENG BOREHOLE
- GOLDRER PIEZOMETER / STAFF GAUGE
- 262.42 STATIC WATER LEVEL (JANUARY 2021)
- (258.99) LOWER SCREENED POTENTIAL (masl)
- - - - - WATER TABLE CONTOUR (masl)
- ▲ WETLAND (BEACON)
- - - - - SITE CONTOURS (1 masl INTERVAL)

REFERENCES AND NOTES

1. MAPPING BASED ON ESRI GEOGRAPHY NETWORK OBM FEATURES AND CLIENT CAD COMPILATIONS
2. WETLAND AND ECOLOGICAL FEATURES, BEACON, FEBRUARY 2021
3. MAPPED FEATURES AND LOCATIONS ARE APPROXIMATE AND NOT TO SCALE
4. BETWEEN THE WELLS AND TEST WELLS, CONTOURED SURFACES ARE NOT PROVEN.
5. LOWER SCREENED POTENTIALS (LEVELS IN BRACKETS) NOT USED FOR INTERPOLATION.

CLIENT
SHINING HILL ESTATES COLLECTION INC.
 C/O SCS CONSULTING GROUP LTD.

CONSULTANT



| | |
|------------|------------|
| YYYY-MM-DD | 2021-03-09 |
| DESIGNED | |
| PREPARED | JPR |
| REVIEWED | JG |
| APPROVED | CMK |

PROJECT
HYDROGEOLOGICAL INVESTIGATION
 SHINING HILL (PHASE 3)
 162, 306, 370, 434 & 488 ST. JOHN'S SIDEROAD WEST, AURORA

TITLE
WATER TABLE JANUARY 2021

| | | | |
|-------------|---------|------|--------|
| PROJECT NO. | CONTROL | REV. | FIGURE |
| 20360612 | 0001 | --- | 8 |



25 mm IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM A4/B

APPENDIX A

Important Information and Limitations of this Report

IMPORTANT INFORMATION AND LIMITATIONS OF THIS REPORT

Standard of Care: Golder Associates Ltd. (Golder) has prepared this report in a manner consistent with that level of care and skill ordinarily exercised by members of the engineering and science professions currently practicing under similar conditions in the jurisdiction in which the services are provided, subject to the time limits and physical constraints applicable to this report. No other warranty, expressed or implied is made.

Basis and Use of the Report: This report has been prepared for the specific site, design objective, development and purpose described to Golder by the Client. The factual data, interpretations and recommendations pertain to a specific project as described in this report and are not applicable to any other project or site location. Any change of site conditions, purpose, development plans or if the project is not initiated within eighteen months of the date of the report may alter the validity of the report. Golder cannot be responsible for use of this report, or portions thereof, unless Golder is requested to review and, if necessary, revise the report.

The information, recommendations and opinions expressed in this report are for the sole benefit of the Client. No other party may use or rely on this report or any portion thereof without Golder's express written consent. If the report was prepared to be included for a specific permit application process, then upon the reasonable request of the client, Golder may authorize in writing the use of this report by the regulatory agency as an Approved User for the specific and identified purpose of the applicable permit review process. Any other use of this report by others is prohibited and is without responsibility to Golder. The report, all plans, data, drawings and other documents as well as all electronic media prepared by Golder are considered its professional work product and shall remain the copyright property of Golder, who authorizes only the Client and Approved Users to make copies of the report, but only in such quantities as are reasonably necessary for the use of the report by those parties. The Client and Approved Users may not give, lend, sell, or otherwise make available the report or any portion thereof to any other party without the express written permission of Golder. The Client acknowledges that electronic media is susceptible to unauthorized modification, deterioration and incompatibility and therefore the Client cannot rely upon the electronic media versions of Golder's report or other work products.

The report is of a summary nature and is not intended to stand alone without reference to the instructions given to Golder by the Client, communications between Golder and the Client, and to any other reports prepared by Golder for the Client relative to the specific site described in the report. In order to properly understand the suggestions, recommendations and opinions expressed in this report, reference must be made to the whole of the report. Golder cannot be responsible for use of portions of the report without reference to the entire report.

Unless otherwise stated, the suggestions, recommendations and opinions given in this report are intended only for the guidance of the Client in the design of the specific project. The extent and detail of investigations, including the number of test holes, necessary to determine all of the relevant conditions which may affect construction costs would normally be greater than has been carried out for design purposes. Contractors bidding on, or undertaking the work, should rely on their own investigations, as well as their own interpretations of the factual data presented in the report, as to how subsurface conditions may affect their work, including but not limited to proposed construction techniques, schedule, safety and equipment capabilities.

Soil, Rock and Ground water Conditions: Classification and identification of soils, rocks, and geologic units have been based on commonly accepted methods employed in the practice of geotechnical engineering and related disciplines. Classification and identification of the type and condition of these materials or units involves judgment, and boundaries between different soil, rock or geologic types or units may be transitional rather than abrupt. Accordingly, Golder does not warrant or guarantee the exactness of the descriptions.

IMPORTANT INFORMATION AND LIMITATIONS OF THIS REPORT

Special risks occur whenever engineering or related disciplines are applied to identify subsurface conditions and even a comprehensive investigation, sampling and testing program may fail to detect all or certain subsurface conditions. The environmental, geologic, geotechnical, geochemical and hydrogeologic conditions that Golder interprets to exist between and beyond sampling points may differ from those that actually exist. In addition to soil variability, fill of variable physical and chemical composition can be present over portions of the site or on adjacent properties. The professional services retained for this project include only the geotechnical aspects of the subsurface conditions at the site, unless otherwise specifically stated and identified in the report. The presence or implication(s) of possible surface and/or subsurface contamination resulting from previous activities or uses of the site and/or resulting from the introduction onto the site of materials from off-site sources are outside the terms of reference for this project and have not been investigated or addressed.

Soil and groundwater conditions shown in the factual data and described in the report are the observed conditions at the time of their determination or measurement. Unless otherwise noted, those conditions form the basis of the recommendations in the report. Groundwater conditions may vary between and beyond reported locations and can be affected by annual, seasonal and meteorological conditions. The condition of the soil, rock and groundwater may be significantly altered by construction activities (traffic, excavation, groundwater level lowering, pile driving, blasting, etc.) on the site or on adjacent sites. Excavation may expose the soils to changes due to wetting, drying or frost. Unless otherwise indicated the soil must be protected from these changes during construction.

Sample Disposal: Golder will dispose of all uncontaminated soil and/or rock samples 90 days following issue of this report or, upon written request of the Client, will store uncontaminated samples and materials at the Client's expense. In the event that actual contaminated soils, fills or groundwater are encountered or are inferred to be present, all contaminated samples shall remain the property and responsibility of the Client for proper disposal.

Follow-Up and Construction Services: All details of the design were not known at the time of submission of Golder's report. Golder should be retained to review the final design, project plans and documents prior to construction, to confirm that they are consistent with the intent of Golder's report.


During construction, Golder should be retained to perform sufficient and timely observations of encountered conditions to confirm and document that the subsurface conditions do not materially differ from those interpreted conditions considered in the preparation of Golder's report and to confirm and document that construction activities do not adversely affect the suggestions, recommendations and opinions contained in Golder's report. Adequate field review, observation and testing during construction are necessary for Golder to be able to provide letters of assurance, in accordance with the requirements of many regulatory authorities. In cases where this recommendation is not followed, Golder's responsibility is limited to interpreting accurately the information encountered at the borehole locations, at the time of their initial determination or measurement during the preparation of the Report.

Changed Conditions and Drainage: Where conditions encountered at the site differ significantly from those anticipated in this report, either due to natural variability of subsurface conditions or construction activities, it is a condition of this report that Golder be notified of any changes and be provided with an opportunity to review or revise the recommendations within this report. Recognition of changed soil and rock conditions requires experience and it is recommended that Golder be employed to visit the site with sufficient frequency to detect if conditions have changed significantly.

Drainage of subsurface water is commonly required either for temporary or permanent installations for the project. Improper design or construction of drainage or dewatering can have serious consequences. Golder takes no responsibility for the effects of drainage unless specifically involved in the detailed design and construction monitoring of the system.


APPENDIX B

Supporting Documentation



DRAFT PLAN OF SUBDIVISION

Part of Lot 86, Concession 1
Town of Aurora
Regional Municipality of York



SCHEDULE OF LAND USE

| LOT / BLOCK | LAND USE | UNITS | AREA |
|--------------|---|-----------|--------------|
| 1-79 | Single Detached Min. 15.24m | □ 31 | 2.01 |
| | Single Detached Min. 13.70m | + 29 | 1.59 |
| | Single Detached Min. 12.20m | ○ 19 | 0.83 |
| 80-88 | Lane Access Single Detached Min. 13.70m | △ 5 | 0.30 |
| | Lane Access Single Detached Min. 12.20m | ~ 4 | 0.19 |
| 89 | Mid / High Rise Residential | | 0.87 |
| 90 | Saint Anne's School | | 4.28 |
| 91 | Neighbourhood Park | | 1.61 |
| 92 | Natural Heritage / Open Space | | 17.72 |
| 93 | Servicing Block | | 0.02 |
| 94 | Trail Head | | 0.02 |
| 95 | Road Widening | | 0.24 |
| 96-97 | 0.3m Reserves | | 0.01 |
| Street A | 23.0m Right of Way 436m | | 1.02 |
| Street B-C | 18.0m Right of Way 420m | | 0.81 |
| Street B | 15.0m Right of Way 108m | | 0.16 |
| Lane A | 9.2m Right of Way 141m | | 0.14 |
| TOTAL | | 88 | 31.79 |

OWNER'S AUTHORIZATION

I hereby authorize Malone Given Parsons Ltd. to prepare and submit this Draft Plan of Subdivision to the Town of Aurora.

Angelo DeGasperis _____ Date _____

SURVEYOR'S CERTIFICATE

I hereby certify that the boundaries of the lands to be subdivided and their relationship to the adjacent lands are correctly shown.

Neil A. LeGrow _____ Date _____

ADDITIONAL INFORMATION

AS REQUIRED UNDER SECTION 51(17) OF THE PLANNING ACT, CHAPTER P.13(R.S.O. 1990).

(a),(e),(f),(g),(j),(l) - As shown of the Draft Plan.
 (b),(c) - As shown on the Draft and Key Plan.
 (d) - Land to be used in accordance with the Schedule of Land Use.
 (i) - Soil is clay loam and sandy loam.
 (h),(k) - Full municipal services to be provided.

Prepared by:


140 Renfrew Drive, Suite 201
Markham, Ontario, L3R 6B3
Tel: (905) 513-0170
www.mgp.ca

Prepared for:

SHINING HILL ESTATE COLLECTION INC.

Date: March 2, 2021 Project No.: 15-2374

| Code | Wetland Communities |
|----------------------|--|
| MAM2 | Mineral Meadow Marsh |
| MAM2-2 | Reed-canary Grass Mineral Meadow Marsh |
| MAS2-1 | Cattail Mineral Shallow Marsh |
| OAO | Open Aquatic |
| SWC1-1 | White Cedar Mineral Coniferous Swamp |
| SWD4-1 | Willow Mineral Deciduous Swamp |
| SWM1-1 | White Cedar - Hardwood Mineral Mixed Swamp |
| SWT2 | Mineral Thicket Swamp |
| SWT2-2 | Willow Mineral Thicket Swamp |
| Forest Communities | |
| FOC1 | Dry - Fresh Pine Coniferous Forest |
| FOC2-2 | Dry - Fresh White Cedar Coniferous Forest |
| FOC3-1 | Fresh - Moist Hemlock Coniferous Forest |
| FOD4 | Dry - Fresh Deciduous Forest |
| FOD5 | Dry - Fresh Sugar Maple Deciduous Forest |
| FOD7 | Fresh - Moist Lowland Deciduous Forest |
| FOM | Mixed Forest |
| FOM3-2 | Dry - Fresh Sugar Maple - Hemlock Mixed Forest |
| Cultural Communities | |
| CUM1 | Mineral Cultural Meadow |
| CUT1 | Mineral Cultural Thicket |
| CUP1-3 | Black Walnut Deciduous Plantation |
| CUP3 | Coniferous Plantations |
| CUP3-3 | Scotch Pine Coniferous Plantation |
| Other Communities | |
| ANT | Anthropogenic |
| HE | Hedgerow |



Existing Conditions Figure 2A

Shining Hill Estate Collection Inc.

Legend


- Study Area
- Staked Dripline (LSRCA, July 21, 2020)
- Long Term Stable Top of Slope (Soil Engineers Ltd, 2020)
- Watercourse (MNRF 2019)
- Staked Dripline (LSRCA 24 Aug 2015)
- Staked Top of Slope (LSRCA 24 Aug 2015)
- Chimney Crayfish Locations
- ELC Communities
- Municipal Boundary (MNRF 2019)
- Regional Floodline (LSRCA)
- Proposed Regional Floodline (Schaeffers Consulting Engineers, 2020)
- Nesting Chimney Swift
- Wetlands (Beacon 2020)
- Amphibian Monitoring Locations
- Culvert Location
- Oak Ridges Moraine Boundary (MNRF 2020)

Butternut Locations


- Category 1
- Category 2

BEACON ENVIRONMENTAL Project: 220166
Last Revised: March, 2021

Client: Shining Hill Estate Collection Inc. Prepared by: BD
Checked by: CS




Contains information licensed under the Open Government License—Ontario
Orthoimagery Basemap: 2019 (FBS)



| Code | Wetland Communities |
|------------------------|--|
| MAM2 | Mineral Meadow Marsh |
| MAM2-2 | Reed-cannary Grass Mineral Meadow Marsh |
| MAS2-1 | Cattail Mineral Shallow Marsh |
| OAO | Open Aquatic |
| SWC1-1 | White Cedar Mineral Coniferous Swamp |
| SWD4-1 | Willow Mineral Deciduous Swamp |
| SWM1-1 | White Cedar - Hardwood Mineral Mixed Swamp |
| SWT2 | Mineral Thicket Swamp |
| SWT2-2 | Willow Mineral Thicket Swamp |
| Forest Communities | |
| FOC1 | Dry - Fresh Pine Coniferous Forest |
| FOC2-2 | Dry - Fresh White Cedar Coniferous Forest |
| FOC3-1 | Fresh - Moist Hemlock Coniferous Forest |
| FOD4 | Dry - Fresh Deciduous Forest |
| FOD5 | Dry - Fresh Sugar Maple Deciduous Forest |
| FOD7 | Fresh - Moist Lowland Deciduous Forest |
| FOM | Mixed Forest |
| FOM3-2 | Dry - Fresh Sugar Maple - Hemlock Mixed Forest |
| Cultural Communities | |
| CUM1 | Mineral Cultural Meadow |
| CUT1 | Mineral Cultural Thicket |
| CUP1-3 | Black Walnut Deciduous Plantation |
| Coniferous Plantations | |
| CUP3 | Coniferous Plantations |
| CUP3-3 | Scotch Pine Coniferous Plantation |
| Other Communities | |
| ANT | Anthropogenic |
| HE | Hedgerow |

| | |
|---|---|
| Existing Conditions | Figure 2B |
| Shining Hill Estate Collection Inc. | |
| Legend | |
| | Study Area |
| | Staked Dripline (LSRCA, July 21, 2020) |
| | Long Term Stable Top of Slope (Soil Engineers Ltd. 2020) |
| | Watercourse (MNRF 2019) |
| | Chimney Crayfish Locations |
| | ELC Communities |
| | Municipal Boundary (MNRF 2019) |
| | Regional Floodline (LSRCA) |
| | Proposed Regional Floodline (Schaeffers Consulting Engineers, 2020) |
| | Wetlands (Beacon 2020) |
| | Amphibian Monitoring Locations |
| | Culvert Location |
| | Nesting Chimney Swift |
| | Oak Ridges Moraine Boundary (MNRF 2020) |
| Butternut Locations | |
| | Category 1 |
| | Category 2 |
| Project: 220166 Last Revised: March, 2021 | |
| Client: Shining Hill Estate Collection Inc. Prepared by: BD Checked by: CS | |
| 1:2,550 | 0 50 100 m |
| Contains information licensed under the Open Government License—Ontario Orthoimagery Basemap: 2019 (FBS) | |



- LEGEND:**
- MUNICIPAL BOUNDARY
 - LIMIT OF DEVELOPMENT
 - EXISTING CONTOUR AND ELEVATION
 - WETLAND BOUNDARY
 - STORM DRAINAGE BOUNDARY
 - TIME TO PEAK LENGTH
 - TIME TO PEAK ELEVATION
 - OVERLAND FLOW DIRECTION
 - CATCHMENT ID
 - DRAINAGE AREA (HECTARES)


30 CENTURIAN DRIVE, SUITE 100
 MARKHAM, ONTARIO L3R 8B8
 TEL: (905) 475-1900
 FAX: (905) 475-8335

**SHINING HILL ESTATES
 COLLECTION INC.**

**SHINING HILL ESTATES
 PHASE 3 - FSSR (AURORA)**

EXISTING STORM DRAINAGE

| | | | |
|--------------|-------------|-------------|------------|
| DESIGNED BY: | B.B.O. | CHECKED BY: | S.E.K. |
| SCALE: | 1:2000 | DATE: | MARCH 2021 |
| PROJECT No: | 2183 | FIGURE No: | 2.1 |



LEGEND:

- MUNICIPAL BOUNDARY
- LIMIT OF DEVELOPMENT
- EXISTING CONTOUR AND ELEVATION
- MAJOR SYSTEM - OVERLAND FLOW
- MINOR SYSTEM - STORM SEWER
- WETLAND BOUNDARY
- STORM DRAINAGE BOUNDARY
- EXTERNAL STORM DRAINAGE BOUNDARY
- 100 YEAR CAPTURE LOCATION
- DRAINAGE AREA (HECTARES)
- RUNOFF COEFFICIENT
- CATCHMENT ID
- EXTERNAL CATCHMENT ID
- DRAINAGE AREA


*NOTE: LAYOUT IS SCHEMATIC ONLY, DETAILS TO BE PROVIDED AT DETAILED DESIGN STAGE.

30 CENTURIAN DRIVE, SUITE 100
 MARKHAM, ONTARIO L3R 8B8
 TEL: (905) 475-1900
 FAX: (905) 475-8335

**SHINING HILL ESTATES
 COLLECTION INC.
 SHINING HILL ESTATES
 PHASE 3 - FSSR (AURORA)**

PROPOSED STORM DRAINAGE

| | |
|---------------------|--------------------|
| DESIGNED BY: B.B.O. | CHECKED BY: S.E.K. |
| SCALE: 1:2000 | DATE: MARCH 2021 |
| PROJECT No: 2183 | FIGURE No: 2.2 |



LEGEND:


| | |
|--|---|
| | LIMIT OF DEVELOPMENT |
| | MUNICIPAL BOUNDARY |
| | STORM SEWER |
| | SUPERPIPE STORM SEWER |
| | SANITARY SEWER |
| | EXISTING SANITARY SEWER |
| | WATERMAIN |
| | EXISTING WATERMAIN |
| | REAR YARD CATCHBASIN |
| | PROPOSED UNDERGROUND STORAGE |
| | METER CHAMBER AND PRESSURE REDUCING VALVE |
| | 100 YEAR CAPTURE LOCATION |

*NOTE: LAYOUT IS SCHEMATIC ONLY. DETAILS TO BE PROVIDED AT DETAILED DESIGN STAGE.









SGS consulting group Ltd
 30 CENTURIAN DRIVE, SUITE 100
 MARKHAM, ONTARIO L3R 8B8
 TEL: (905) 475-1900
 FAX: (905) 475-8335

SHINING HILL ESTATES COLLECTION INC.
SHINING HILL ESTATES PHASE 3 - FSSR (AURORA)
PROPOSED SERVICING PLAN

| | |
|---------------------|--------------------|
| DESIGNED BY: B.B.O. | CHECKED BY: S.E.K. |
| SCALE: 1:1000 | DATE: MARCH 2021 |
| PROJECT No: 2183 | FIGURE No: 2.3 |



LEGEND:

-  MUNICIPAL BOUNDARY
-  LIMIT OF DEVELOPMENT
-  STORM DRAINAGE BOUNDARY
-  REAR YARD INFILTRATION TRENCH (25 mm/imp-ha)
-  CATCHBASIN INFILTRATION SYSTEM
-  CATCHBASIN FILTRATION SYSTEM
-  ON-SITE INFILTRATION (25 mm/imp-ha)
-  BIOSWALE (25 mm/imp-ha)

*NOTE: LAYOUT IS SCHEMATIC ONLY, DETAILS TO BE PROVIDED AT DETAILED DESIGN STAGE.


 30 CENTURIAN DRIVE, SUITE 100
 MARKHAM, ONTARIO L3R 8B8
 TEL: (905) 475-1900
 FAX: (905) 475-8335

**SHINING HILL ESTATES
 COLLECTION INC.**


**SHINING HILL ESTATES
 PHASE 3 - FSSR (AURORA)**

LID PLAN


| | |
|----------------------------|--------------------------|
| DESIGNED BY: B.B.O. | CHECKED BY: S.E.K. |
| SCALE: 1:2000 | DATE: MARCH 2021 |
| PROJECT No: 2183 | FIGURE No: 2.5 |



SPLIT DRAINING LOTS PLAN
SCALE 1:250



SECTION B1-B1
SCALE 1:250



SECTION A1-A1 INFILTRATION TRENCH ASSEMBLY
SCALE 1:50

*NOTE: LAYOUT IS SCHEMATIC ONLY, DETAILS TO BE PROVIDED AT DETAILED DESIGN STAGE.

SHINING HILL ESTATES COLLECTION INC.

LEGEND:


SCS consulting group ltd
30 CENTURIAN DRIVE, SUITE 100
MARKHAM, ONTARIO L3R 8B8
TEL: (905) 475-1900
FAX: (905) 475-8335

SHINING HILL ESTATES PHASE 3 - FSSR (AURORA)

REAR YARD INFILTRATION TRENCH DETAIL

DESIGNED BY: B.B.O. CHECKED BY: S.E.K.
SCALE: AS SHOWN DATE: MARCH 2021

PROJECT No: **2183** FIGURE No: **2.8**



LEGEND:


| | |
|--|--------------------------------|
| | MUNICIPAL BOUNDARY |
| | LIMIT OF DEVELOPMENT |
| | EXISTING CONTOUR AND ELEVATION |
| | PROPOSED CONTOUR |
| | EXISTING ELEVATION |
| | PROPOSED ELEVATION |
| | PROPOSED 3:1 MAX SLOPE |
| | PROPOSED ROAD GRADE |
| | PROPOSED ROAD HIGH / LOW POINT |
| | EXISTING REGULATORY FLOODLINE |
| | FRONT DRAINING LOT |
| | WALKOUT LOT |

NOTE: ALL SINGLE RESIDENTIAL LOTS ARE SPLIT DRAINING UNLESS OTHERWISE NOTED.
 *NOTE: LAYOUT IS SCHEMATIC ONLY. DETAILS TO BE PROVIDED AT DETAILED DESIGN STAGE.

SGS consulting group Ltd
 30 CENTURIAN DRIVE, SUITE 100
 MARKHAM, ONTARIO L3R 8B8
 TEL: (905) 475-1900
 FAX: (905) 475-8335


**SHINING HILL ESTATES
 COLLECTION INC.
 SHINING HILL ESTATES
 PHASE 3 - FSSR (AURORA)
 PRELIMINARY GRADING PLAN**

| | |
|---------------------|--------------------|
| DESIGNED BY: B.B.O. | CHECKED BY: S.E.K. |
| SCALE: 1:1000 | DATE: MARCH 2021 |
| PROJECT No: 2183 | FIGURE No: 5.1 |



PRELIMINARY FILTRATION TRENCH - PROFILE VIEW

SCALE: N.T.S.



PRELIMINARY FILTRATION TRENCH CROSS-SECTION

SCALE: N.T.S.

*NOTE: LAYOUT IS SCHEMATIC ONLY, DETAILS TO BE PROVIDED AT DETAILED DESIGN STAGE.

SHINING HILL ESTATES
COLLECTION INC.

LEGEND:



30 CENTURIAN DRIVE, SUITE 100
MARKHAM, ONTARIO L3R 8B8
TEL: (905) 475-1900
FAX: (905) 475-8335

SHINING HILL ESTATES
PHASE 3 - FSSR (AURORA)

CATCHBASIN FILTRATION
TRENCH DETAIL

DESIGNED BY: B.B.O.

CHECKED BY: S.E.K.

PROJECT No:


FIGURE No:

SCALE: AS SHOWN

DATE: MARCH 2021

2183

6.7



PRELIMINARY INFILTRATION TRENCH - PROFILE VIEW

SCALE: N.T.S.

*NOTE: LAYOUT IS SCHEMATIC ONLY, DETAILS TO BE PROVIDED AT DETAILED DESIGN STAGE.

**SHINING HILL ESTATES
COLLECTION INC.**

LEGEND:

SCS consulting group ltd
 30 CENTURIAN DRIVE, SUITE 100
 MARKHAM, ONTARIO L3R 8B8
 TEL: (905) 475-1900
 FAX: (905) 475-8335

**SHINING HILL ESTATES
PHASE 3 - FSSR (AURORA)**

**CATCHBASIN INFILTRATION
TRENCH DETAIL**

| | | | |
|--------------|----------|-------------|------------|
| DESIGNED BY: | B.B.O. | CHECKED BY: | S.E.K. |
| SCALE: | AS SHOWN | DATE: | MARCH 2021 |

PROJECT No:
2183

FIGURE No:
6.8

APPENDIX C

MECP Water Well Records

| LABEL | CON LOT | DATE mmm-yr | EASTING NORTHING | ELEV masl | WTR FND mbgl Qu | CR TOP LEN mbgl m | SWL mbgl | RATE L/min | TIME min | PL mbgl | DRILLER METHOD | TYPE STAT | WELL NAME DESCRIPTION OF MATERIALS |
|---------|---------|----------------|---------------------|--------------|--------------------|----------------------|-------------|---------------|-------------|------------|-------------------|--------------|--|
| 6901579 | 1 86 | Aug-57 | 621280 4874782 | 288.6 | 94.5 Fr 6.1 Fr | 107.0 -1.5 | 21.3 | 14 | 2160 | 29.0 | 4823 CT | WS DO | MOE# 6901579 0.0 TPSSL 0.3 YLLW CLAY MSND 6.1 SILT MSND 10.7 GREY CLAY 91.4 GRVL 91.7 BLUE CLAY 94.5 SILT MSND 104.5 MSND GRVL 108.2 |
| 6901581 | 1 86 | Nov-61 | 622013 4874963 | 263.0 | 47.9 Fr | 48.5 -1.2 | 9.1 | 23 | 480 | 21.3 | 2310 CT | WS PU | MOE# 6901581 0.0 TPSSL 0.3 CLAY MSND 4.6 BLUE CLAY 45.1 CLAY GRVL 47.9 MSND 50.0 |
| 6901582 | 1 86 | Jan-62 | 621090 4874655 | 301.8 | 8.5 Fr | | 6.1 | 9 | | | 4102 CT | WS ST | MOE# 6901582 0.0 BLUE CLAY 8.5 GRVL 10.1 |
| 6901584 | 1 87 | Apr-59 | 622190 4875492 | 254.8 | 75.6 Fr | 76.2 -1.2 | 1.2 | 55 | 300 | 2.7 | 2310 CT | WS DO | MOE# 6901584 0.0 YLLW CLAY 25.9 STNS 48.8 GREY CLAY 73.2 CLAY 75.6 MSND 77.4 |
| 6901586 | 1 87 | Jul-49 | 621685 4875541 | 265.2 | 76.2 Fr | 75.0 -1.2 | FLW | 27 | | | 2310 CT | WS DO | MOE# 6901586 0.0 CLAY 33.5 CLAY BLDR 45.7 CLAY 74.7 GRVL 76.2 |
| 6901587 | 1 87 | Jul-62 | 622024 4875476 | 249.0 | 9.1 Fr | | 3.0 | 9 | | | 4102 BR ST | WS ST | MOE# 6901587 0.0 BLUE CLAY 9.1 GREY CLAY MSND 13.7 |
| 6901589 | 1 87 | Oct-63 | 622310 4875533 | 250.5 | 69.2 Fr | 70.1 -1.2 | 4.6 | 36 | 60 | 24.4 | 2310 CT | WS DO | MOE# 6901589 0.0 TPSSL 0.6 GREY CLAY 6.7 BLUE CLAY 35.1 MSND GRVL CLAY 40.2 CLAY MSND 53.3 BLUE CLAY 67.1 CLAY GRVL 69.2 CSND 71.6 |
| 6907445 | 1 85 | Aug-62 | 622681 4874898 | 260.0 | 29.0 Fr | 31.7 -2.4 | 10.1 | 68 | 120 | 15.2 | 2310 CT | WS DO | MOE# 6907445 0.0 RED CLAY 4.3 GREY CLAY 21.3 CLAY STNS 29.0 GRVL 34.1 |
| 6908544 | 1 87 | Apr-68 | 622232 4875671 | 256.3 | 74.7 Fr | 73.8 -2.1 | 8.5 | 45 | 120 | 15.2 | 2310 CT | WS DO | MOE# 6908544 0.0 GREY CLAY 4.3 BLUE CLAY 32.3 BLUE CLAY GRVL STNS 61.9 BLUE CLAY 74.7 MSND 75.9 |
| 6910570 | 1 86 | Apr-71 | 620962 4874701 | 306.0 | 166.1 Fr | | 68.6 | 23 | 540 | 82.3 | 1663 CT | WS DO | MOE# 6910570 0.0 BRWN MSND CLAY 10.7 BRWN GRVL MSND 21.3 BLUE CLAY STNS 141.7 BLUE CLAY MSND 147.8 BLUE CLAY 165.2 BLCK MSND SILT CLAY 167.0 |
| 6913488 | 1 86 | Sep-76 | 622052 4875111 | 251.8 | 44.8 Fr | 49.4 -0.9 | 9.1 | 23 | 4800 | 48.2 | 2341 CT | WS PU | MOE# 6913488 0.0 BRWN SAND STNS 4.6 BLUE CLAY 44.8 CLAY GRVL 50.0 SAND 51.5 |
| 6915585 | 1 86 | Sep-80 | 622012 4875021 | 260.9 | 50.3 - | 52.1 -2.7 | 20.4 | 45 | 300 | 25.0 | 3108 RC | WS PU | MOE# 6915585 0.0 PRDR 49.7 SAND 55.2 |
| 6916809 | 1 86 | Nov-83 | 621412 4874821 | 280.1 | 112.8 - | 114.6 -1.8 | 56.7 | 23 | 240 | 85.3 | 3108 RC | WS DO | MOE# 6916809 0.0 TPSSL 0.6 BRWN SAND CLAY 7.9 BLUE CLAY 24.7 BLUE SILT 33.8 BLUE CLAY 103.3 BLUE SAND CLAY 104.9 BLUE CLAY 112.8 BLUE FSND VERY 117.0 |

| LABEL | CON LOT | DATE mmm-yr | EASTING NORTHING | ELEV masl | WTR FND mbgl Qu | CR TOP LEN mbgl m | SWL mbgl | RATE L/min | TIME min | PL mbgl | DRILLER METHOD | TYPE STAT | WELL NAME DESCRIPTION OF MATERIALS |
|---------|---------|----------------|---------------------|--------------|--------------------|-------------------------|-------------|---------------|-------------|------------|-------------------|--------------|---|
| 6918411 | 1 85 | Dec-86 | 622617 4875023 | 255.1 | 89.9 Fr | 89.9 -10.7 | 21.3 | 909 | 480 | 22.9 | 1413 RC | WS MU | MOE# 6918411 0.0 BRWN CLAY DNSE 3.7 GREY CLAY SILT SOFT 19.8 BRWN GRVL SAND PCKD 22.9 GREY CLAY STNS HARD 32.0 GREY CLAY STNS HARD 53.9 GREY CLAY DNSE 68.9 GREY SAND MGRD CLN 81.7 GREY SAND PCKD 86.0 GREY SAND LOOS 88.4 GREY GRVL STNS HARD 89.9 GREY GRVL CLN LOOS 94.5 GREY GRVL SAND CLN 96.3 |
| 6918439 | 1 85 | Jan-87 | 622623 4875028 | 255.1 | 120.4 Fr | 88.4 -6.1 121.9 -3.7 | 21.3 | 227 | 480 | 45.7 | 1413 RC | TH NU | MOE# 6918439 0.0 BRWN CLAY DNSE 3.7 GREY CLAY SILT SOFT 19.8 BRWN GRVL SAND PCKD 22.9 GREY CLAY STNS HARD 32.0 GREY CLAY STNS HARD 53.9 GREY CLAY DNSE 68.6 BRWN SAND CLN LOOS 80.8 GREY CLAY SAND PCKD 86.0 GREY SAND CLN LOOS 86.9 GREY GRVL SAND CLN 95.1 GREY GRVL PCKD 109.1 GREY GRVL CLN LOOS 111.3 GREY GRVL 113.4 GREY CLAY DNSE 114.3 GREY GRVL SAND PCKD 115.8 GREY GRVL SAND CLN 117.3 GREY GRVL SAND PCKD 119.5 GREY CLAY SAND PCKD 120.4 GREY SAND CLN 121.3 GREY GRVL SAND CGRD 124.4 GREY CLAY STNS CMTD 126.5 |
| 6918544 | 1 85 | Feb-87 | 622614 4875023 | 255.1 | 86.9 Fr | 88.4 -6.1 | 21.3 | 2728 | 240 | 48.8 | 1413 RC | TH NU | MOE# 6918544 0.0 BRWN CLAY DNSE 3.7 GREY CLAY SILT SOFT 19.8 BRWN GRVL SAND PCKD 22.9 GREY CLAY STNS HARD 32.0 GREY CLAY STNS HARD 53.9 GREY CLAY DNSE 68.6 BRWN SAND CLN LOOS 80.8 GREY CLAY SAND PCKD 86.0 GREY SAND CLN LOOS 86.9 GREY GRVL SAND LOOS 94.5 |
| 6918645 | 1 85 | Sep-86 | 622350 4874460 | 253.0 | 29.3 Fr | 27.4 -1.8 | 6.1 | 27 | 130 | 29.0 | 5459 CT | WS DO | MOE# 6918645 0.0 BRWN CLAY 5.2 BLUE CLAY SOFT 29.3 BRWN SAND MGRD 31.1 |
| 6923894 | 1 86 | May-97 | 621975 4875041 | 264.6 | 81.4 Fr | 80.5 -0.9 | NR | 114 | 150 | 76.2 | 1413 RA | WS DO | MOE# 6923894 0.0 BRWN CLAY HARD 5.2 GREY CLAY SOFT 42.7 BRWN CLAY SAND LYRD 50.9 GREY CLAY HARD 55.8 BRWN SAND GRVL CMTD 59.1 GREY CLAY STNS HARD 79.9 BRWN FSND CLN 81.4 |
| 7130451 | 1 87 | Jun-08 | 620911 4874935 | 285.6 | 102.7 Un | 107.6 -1.5 | 77.4 | 50 | 60 | 91.1 | 1663 RC | WS DO | MOE# 7130451 TAG#A075076 0.0 BRWN SAND 4.9 BRWN CLAY SILT 7.0 GREY CLAY GRVL 23.8 BRWN SAND CLAY 29.6 GREY SILT CLAY 82.9 BRWN SAND STNS CLAY 86.3 GREY CLAY GRVL 102.7 GREY FSND SILT LYRD 109.1 |
| 7152094 | 1 86 | Sep-10 | 622163 4875162 | 249.0 | | 75.0 -1.8 | 22.9 | | 2880 | 22.9 | 6300 RC | WS - | MOE# 7152094 TAG#A081679 0.0 TPLS 0.6 BRWN CLAY 4.9 BLUE CLAY HARD 24.4 GRVL 25.3 BLUE CLAY SOFT 36.6 BLUE CLAY SOFT 42.7 BLUE CLAY HARD 73.8 SAND CLN 76.8 BLUE CLAY HARD 85.3 |

| LABEL | CON LOT | DATE mmm-yr | EASTING NORTHING | ELEV masl | WTR FND mbgl Qu | CR TOP LEN mbgl m | SWL mbgl | RATE L/min | TIME min | PL DRILLER mbgl METHOD | TYPE STAT | WELL NAME DESCRIPTION OF MATERIALS |
|---------|---------|----------------|---------------------|--------------|--------------------|------------------------|-------------|---------------|-------------|---------------------------|--------------|---|
| 7190773 | 1 85 | Oct-12 | 622613 4875032 | 255.1 | | 29.0 0.0 | NR | | | 5459 RA | OW MO | MOE# 7190773 TAG#A124709 0.0 GREY FILL SOFT 2.4 GREY CLAY SOFT 7.6 GREY CLAY SILT LYRD 19.2 RED BLDR DNSE 19.5 GREY MSND GRVL SILT 22.9 GREY MSND STNS LOOS 24.4 BRWN MSND LOOS 27.4 GREY CSND GRVL LOOS 29.6 |
| 7236984 | | Dec-14 | 622371 4875420 | 249.3 | | | NR | | | 6032 - | - - | MOE# 7236984 TAG#A102044 0.0 |
| 7259668 | 1 86 | Feb-16 | 622397 4875030 | 247.5 | 3.0 Un | 3.0 -1.5 | NR | | | 7147 BR | OW MO | MOE# 7259668 TAG#A198730 0.0 BRWN CLAY SOFT 4.6 |
| 7285109 | | Sep-16 | 622627 4875024 | 255.4 | 10.1 Un | 93.3 -4.3 89.6 -3.0 | 13.7 | 3300 | 4320 | 18.6 7564 RC | WS MU | MOE# 7285109 TAG#A172641 0.0 TPSTL 0.6 BRWN CLAY 6.4 GREY CLAY SOFT 19.8 GREY GRVL SAND 33.5 GREY CLAY GRVL 49.1 GREY CLAY DNSE 67.4 GREY SILT 73.2 GREY FSND 87.8 GREY GRVL SAND 99.7 |
| 7285110 | | Sep-16 | 622627 4875024 | 255.4 | | | NR | | | 7564 - | - - | MOE# 7285110 TAG#A172641 0.0 MSND GRVL 102.7 |
| 7306495 | | Aug-17 | 621091 4874653 | NR | 13.4 Un | 12.2 -3.0 | NR | | | 7247 RC | OW TH | MOE# 7306495 TAG#A201420 0.0 BRWN SILT SAND WTHD 0.6 BRWN SAND SILT DNSE 4.0 BRWN SILT SAND DNSE 15.2 |
| 7309192 | 1 85 | Dec-16 | 622599 4875009 | NR | | 7.6 -3.0 | NR | | | 6032 BR | OW MO | MOE# 7309192 TAG#A194356 0.0 BRWN CLAY SOFT 3.0 GREY CLAY SOFT 10.7 |
| 7326065 | 1 87 | Nov-18 | 622101 4875609 | NR | | | NR | | | 7230 - | - - | MOE# 7326065 TAG#A253727 0.0 |
| GSC2996 | | Jan-01 | 622417 4874820 | 249.9 | | | NR | | | - - | - - | MOE# GSC2996 0.0 SILT CLAY CLYY 2.4 SILT CLAY CLYY 18.6 |
| GSC3000 | | Jan-01 | 622341 4875120 | 253.6 | | | NR | | | - - | - - | MOE# GSC3000 0.0 SILT CLAY CLYY 14.6 SAND SLTY TILL 21.6 |
| GSC3211 | | Jan-01 | 622516 4875020 | 253.6 | | | NR | | | - - | - - | MOE# GSC3211 0.0 SILT CLAY CLYY 1.2 SAND SLTY 1.8 GRVL SAND GRVL 2.7 SILT CLAY CLYY 5.8 |
| YPD1357 | | Jan-13 | 622629 4875020 | 255.4 | | | NR | | | - - | - - | MOE# YPD1357 0.0 BRWN SILT CLAY 6.1 GREY CLAY 15.2 GREY CLAY 18.3 GREY SILT SAND GRVL 24.4 BRWN SAND 29.0 BRWN SAND GRVL 33.5 GREY CLAY HARD 68.0 GREY SAND FGRD 76.2 GREY SAND 79.2 GREY SAND FGRD 86.9 GREY SAND GRVL 99.1 GREY SAND 103.6 GREY SAND 112.8 GREY CLAY 113.4 |
| YPD1366 | | Oct-12 | 622609 4875025 | 255.4 | | 27.4 -1.5 | NR | | | - - | - - | MOE# YPD1366 0.0 GREY CLAY SILT GRVL 68.0 GREY SAND GRVL 68.6 GREY SAND SILT FGRD 69.2 SAND GRVL 70.1 GRVL SAND SILT 70.7 CLAY SILT LYRD 71.6 CLAY SILT 75.3 BRWN FILL 76.8 |
| YPD3668 | | Jan-01 | 621398 4874866 | 275.8 | | | NR | | | - - | - - | MOE# YPD3668 0.0 6.4 SAND 6.7 |

| LABEL | CON LOT | DATE | EASTING NORTHING | ELEV masl | WTR FND mbgl Qu | SCR TOP LEN mbgl m | SWL mbgl | RATE L/min | TIME min | PL DRILLER mbgl METHOD | TYPE STAT | WELL NAME DESCRIPTION OF MATERIALS |
|---------|---------|--------|-------------------|-----------|-----------------|--------------------|----------|------------|----------|------------------------|-----------|--|
| YPD3935 | | Jan-01 | 622584 4875053 | 254.5 | | | NR | | | | - | MOE# YPD3935 0.0 SILT SAND CLAY 3.7 SILT SAND CLAY 19.8 GRVL SAND 22.9 TILL SILT SAND 54.9 SILT SAND CLAY 68.9 SAND SILT 81.7 SAND SILT 86.0 SAND SILT 88.4 GRVL SAND 94.5 GRVL SAND 112.2 TILL CLAY SILT 120.7 TILL CLAY SILT 123.1 GRVL SAND 127.1 TILL CLAY SILT 130.5 CLAY SILT 132.6 ROCK 137.2 |
| YPD4752 | | Jan-01 | 622666 4874969 | 259.4 | | | NR | | | | - | MOE# YPD4752 0.0 SILT SAND CLAY 19.8 TILL SAND SILT 22.9 TILL SILT SAND 54.9 SILT SAND CLAY 68.9 SAND SILT 88.4 GRVL SAND 112.2 TILL CLAY SILT 120.7 TILL SILT SAND 123.1 GRVL SAND 127.1 TILL CLAY SILT 130.5 CLAY SILT 132.6 |

| QUALITY: | | TYPE: | | USE: | | METHOD : | | | |
|----------|------------|-------|--------------------------|------|-----------|----------|--------------|----|---------------------|
| Fr | Fresh | WS | Water Supply | CO | Comercial | NU | Not Used | CT | Cable Tool |
| Mn | Mineral | AQ | Abandoned Quality | DO | Domestic | IR | Irrigation | JT | Jetting |
| Sa | Salty | AS | Abandoned Supply | MU | Municipal | AL | Alteration | RC | Rotary Conventional |
| Su | Sulphur | AB | Abandonment Record | PU | Public | MO | Monitoring | RA | Rotary Air |
| -- | Unrecorded | TH | Test Hole or Observation | ST | Stock | - | Not Recorded | BR | Boring |

Easting and Northings UTM NAD 83 Zone 17, Translated from Recorded UTM NAD, subject to Field Verified Location or Improved Location Accuracy.

Records Copyright Ministry of Environment Queen's Printer. Selected information tabulated to metric with changes and corrections subject to Driller's Records.

APPENDIX D

List of Abbreviations and
Description of Terms

Record of Borehole Sheets
BH101 to BH108
& BH201 to BH206

Plasticity Chart and Grain Size Analysis
(Soil Eng. 2021A and 2021B)

LIST OF ABBREVIATIONS AND DESCRIPTION OF TERMS

The abbreviations and terms commonly employed on the borehole logs and figures, and in the text of the report, are as follows:

SAMPLE TYPES

| | |
|----|---|
| AS | Auger sample |
| CS | Chunk sample |
| DO | Drive open (split spoon) |
| DS | Denison type sample |
| FS | Foil sample |
| RC | Rock core (with size and percentage recovery) |
| ST | Slotted tube |
| TO | Thin-walled, open |
| TP | Thin-walled, piston |
| WS | Wash sample |

SOIL DESCRIPTION

Cohesionless Soils:

| <u>'N'</u> (blows/ft) | <u>Relative Density</u> |
|-----------------------|-------------------------|
| 0 to 4 | very loose |
| 4 to 10 | loose |
| 10 to 30 | compact |
| 30 to 50 | dense |
| over 50 | very dense |

Cohesive Soils:

PENETRATION RESISTANCE

Dynamic Cone Penetration Resistance:

A continuous profile showing the number of blows for each foot of penetration of a 2-inch diameter, 90° point cone driven by a 140-pound hammer falling 30 inches.

Plotted as '—●—'

Undrained Shear Strength (ksf)

| |
|----------------|
| less than 0.25 |
| 0.25 to 0.50 |
| 0.50 to 1.0 |
| 1.0 to 2.0 |
| 2.0 to 4.0 |
| over 4.0 |

'N' (blows/ft)

| |
|----------|
| 0 to 2 |
| 2 to 4 |
| 4 to 8 |
| 8 to 16 |
| 16 to 32 |
| over 32 |

Consistency

| |
|------------|
| very soft |
| soft |
| firm |
| stiff |
| very stiff |
| hard |

Standard Penetration Resistance or 'N' Value:

The number of blows of a 140-pound hammer falling 30 inches required to advance a 2-inch O.D. drive open sampler one foot into undisturbed soil.

Plotted as '○'

Method of Determination of Undrained Shear Strength of Cohesive Soils:

x 0.0 Field vane test in borehole; the number denotes the sensitivity to remoulding

△ Laboratory vane test

□ Compression test in laboratory

For a saturated cohesive soil, the undrained shear strength is taken as one half of the undrained compressive strength

| | |
|----|--|
| WH | Sampler advanced by static weight |
| PH | Sampler advanced by hydraulic pressure |
| PM | Sampler advanced by manual pressure |
| NP | No penetration |

METRIC CONVERSION FACTORS

1 ft = 0.3048 metres
11b = 0.454 kg

1 inch = 25.4 mm
1ksf = 47.88 kPa



Soil Engineers Ltd.

CONSULTING ENGINEERS


GEOTECHNICAL • ENVIRONMENTAL • HYDROGEOLOGICAL • BUILDING SCIENCE

PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 10 and 11, 2020



(Continued on next page)



PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 10 and 11, 2020

| El. (m) Depth (m) | SOIL DESCRIPTION | SAMPLES | | | Depth Scale (m) | Dynamic Cone (blows/30 cm) | | Atterberg Limits | | WATER LEVEL |
|----------------------|---|---------|------|---------|-----------------|----------------------------|----|------------------|----|-------------|
| | | Number | Type | N-Value | | 10 | 30 | 50 | 70 | |
| 10.0 | (Continued) Grey, firm to stiff SILTY CLAY (varved) a trace of sand with silt seams and layers | | | | 10 | | | | | |
| | | 10 | DO | 7 | 11 | ○ | | | | ● 28 |
| | | | | | 12 | | | | | |
| | | 11 | DO | 7 | 13 | ○ | | | | ● 24 |
| | | | | | 14 | | | | | |
| | | 12 | DO | 7 | 15 | ○ | | | | ● 27 |
| | | | | | 16 | | | | | |
| | | 13 | DO | 8 | 17 | ○ | | | | ● 26 |
| | | | | | 18 | | | | | |
| | | 14 | DO | 11 | 19 | ○ | | | | ● 25 |
| 247.8 17.2 | END OF BOREHOLE Installed 50 mm Ø PVC monitoring well to 7.6 m (1.5 m screen) Sand backfill from 5.5 m to 7.6 m Bentonite holeplug from 0.3 m to 5.5 m Provided with a flushmount casing Sealed with 0.3 m concrete to surface with top and bottom caps | | | | 20 | | | | | |




PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 16, 2020




W.L. @ El. 262.1 m in well on September 29, 2020

PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 16, 2020



Cave-in @ El. 265.3 m on completion
W.L. @ El. 265.5 m in well on September 29, 2020




PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 11, 2020



W.L. @ El. 264.6 m in well on September 29, 2020




PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Hollow Stem Augers Washbore with Tri-Cone and Dynamic Cone

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 9, 10, 14 and 15,



(Continued on next page)

No W.L. recorded due to process of washboring to carry out deep borehole
 W.L. @ El. 259.6 m in well on September 29, 2020



JOB NO.: 2008-S135A

LOG OF BOREHOLE NO.: 105


FIGURE NO.: 5

PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Hollow Stem Augers
Washbore with Tri-
Cone and Dynamic
Cone

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 9, 10, 14 and 15,



JOB NO.: 2008-S135A

LOG OF BOREHOLE NO.: 105


FIGURE NO.: 5

PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Hollow Stem Augers
Washbore with Tri-
Cone and Dynamic
Cone

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 9, 10, 14 and 15,



PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Hollow Stem Augers
Washbore with Tri-
Cone and Dynamic
Cone

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 9, 10, 14 and 15,

| El. (m) Depth (m) | SOIL DESCRIPTION | SAMPLES | | | Depth Scale (m) | Dynamic Cone (blows/30 cm) | | Atterberg Limits | | WATER LEVEL |
|----------------------|--|---------|------|---------|-----------------|----------------------------|----------------|------------------|--|-------------|
| | | Number | Type | N-Value | | 10 30 50 70 90 | 10 30 50 70 90 | PL LL | | |
| 30.0 | (Continued) Grey, stiff SILTY CLAY (varved) a trace of sand with silt layers | 23 | DO | 13 | 30 | | | | | |
| 235.9 30.9 | END OF BOREHOLE | | | | 31 | | | | | |
| | DYNAMIC CONE PENETRATION TEST | | | | 32 | | | | | |
| | | | | | 33 | | | | | |
| | | | | | 34 | | | | | |
| | | | | | 35 | | | | | |
| | | | | | 36 | | | | | |
| | | | | | 37 | | | | | |
| 228.7 38.1 | END OF DYNAMIC CONE TEST | | | | 38 | | | | | |
| | Installed 50 mm Ø PVC monitoring well to 16.8 m (3.0 m screen) Sand backfill from 13.1 m to 16.8 m Bentonite holeplug from 0 m to 13.1 m Provided with a 4x4 steel monument casing with top and bottom caps, and lock | | | | 39 | | | | | |
| | | | | | 40 | | | | | |




PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 11 and 14, 2020



(Continued on next page)



JOB NO.: 2008-S135A

LOG OF BOREHOLE NO.: 106

FIGURE NO.: 6

PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 11 and 14, 2020

| El. (m) Depth (m) | SOIL DESCRIPTION | SAMPLES | | | Depth Scale (m) | Dynamic Cone (blows/30 cm) | | Atterberg Limits | | WATER LEVEL |
|----------------------|--|---------|------|---------|-----------------|----------------------------|----|------------------|----|-------------|
| | | Number | Type | N-Value | | 10 | 30 | 50 | 70 | |
| 10.0 | (Continued) Grey, firm to stiff SILTY CLAY (varved) a trace of sand with silt layers | | | | 10 | | | | | |
| | | 10 | DO | 7 | 11 | ○ | | | | ● 24 |
| | | | | | 12 | | | | | |
| | | 11 | DO | 9 | 13 | ○ | | | | ● 28 |
| | | | | | 14 | | | | | |
| | | 12 | DO | 9 | 15 | ○ | | | | ● 25 |
| | | | | | 16 | | | | | |
| | | 13 | DO | 9 | 17 | ○ | | | | ● 21 |
| | | | | | 18 | | | | | |
| | | 14 | DO | 9 | 19 | ○ | | | | ● 24 |
| 248.1 17.2 | END OF BOREHOLE Installed 50 mm Ø PVC monitoring well to 7.6 m (1.5 m screen) Sand backfill from 5.5 m to 7.6 m Bentonite holeplug from 0 m to 5.5 m Provided with a 4x4 steel monument casing with top and bottom caps, and lock | | | | 20 | | | | | |

W.L. @ El. 253.7 m on completion




PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 14, 2020




W.L. @ El. 258.3 m in well on September 29, 2020

PROJECT DESCRIPTION: Proposed Residential Development

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
162 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 15, 2020



Cave-in @ El. 265.8 m on completion
W.L. @ El. 266.1 m in well on September 29, 2020




PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 15, 2020




PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 16, 2020



W.L. @ El. 266.7 m in well on September 29, 2020




PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 16, 2020




PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Hollow Stem Augers and Washbore with Tri-Cone

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 17 to 21, 2020



(Continued on next page)




PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Hollow Stem Augers and Washbore with Tri-Cone

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 17 to 21, 2020



JOB NO.: 2008-S135B

LOG OF BOREHOLE NO.: 204


FIGURE NO.: 4

PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Hollow Stem Augers and Washbore with Tri-Cone

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 17 to 21, 2020




Soil Engineers Ltd.

PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 17, 2020




W.L. @ El. 270.3 m in well on September 29, 2020

PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Hollow Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 16 to 17, 2020



(Continued on next page)



JOB NO.: 2008-S135B

LOG OF BOREHOLE NO.: 206D


FIGURE NO.: 6A

PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Hollow Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 16 to 17, 2020



PROJECT DESCRIPTION: Proposed School Block

METHOD OF BORING: Solid Stem Augers

PROJECT LOCATION: Shining Hill Phase 3
306 St. John's Sideroad
Town of Aurora

DRILLING DATE: September 17, 2020

| El. (m) Depth (m) | SOIL DESCRIPTION | SAMPLES | | | Depth Scale (m) | ● Dynamic Cone (blows/30 cm) 10 30 50 70 90 | Atterberg Limits PL LL | WATER LEVEL |
|----------------------|--|---------|------|---------|-----------------|--|--|-------------|
| | | Number | Type | N-Value | | ✕ Shear Strength (kN/m²) 50 100 150 200 | ○ Penetration Resistance (blows/30 cm) 10 30 50 70 90 | |
| 273.3 | Ground Surface | | | | | | | |
| 0.0 | STRAIGHT AUGERING FOR INSTALLATION OF NESTED WELL | | | | 0 | | | |
| | | | | | 1 | | | |
| | | | | | 2 | | | |
| | | | | | 3 | | | |
| | | | | | 4 | | | |
| | | | | | 5 | | | |
| | | | | | 6 | | | |
| 265.7 | END OF BOREHOLE Installed 50 mm Ø PVC monitoring well to 7.6 m (1.5 m screen) Sand backfill from 5.5 m to 7.6 m Bentonite holeplug from 0 m to 5.5 m Provided with a 4x4 steel monument casing with top and bottom caps, and lock | | | | 7 | | | |
| 7.6 | | | | | 8 | | | |
| | | | | | 9 | | | |
| | | | | | 10 | | | |

W.L. @ El. 269.4 m in well on September 29, 2020




U.S. BUREAU OF SOILS CLASSIFICATION

| | | | | | | | | |
|--------|--|------|--------|--------|------|---------|------|------|
| GRAVEL | | | SAND | | | | SILT | CLAY |
| COARSE | | FINE | COARSE | MEDIUM | FINE | V. FINE | | |

UNIFIED SOIL CLASSIFICATION

| | | | | | | | |
|--------|--|------|--------|--------|------|--|-------------|
| GRAVEL | | | SAND | | | | SILT & CLAY |
| COARSE | | FINE | COARSE | MEDIUM | FINE | | |



Project: Proposed Residential Development
 Location: Shining Hill Phase 3
 162 St. John's Sideroad, Town of Aurora
 Borehole No: 101 102 105
 Sample No: 9 7 14
 Depth (m): 9.4 4.8 17.0
 Elevation (m): 255.6 260.1 249.8

| BH./Sa. | 101/9 | 102/7 | 105/14 |
|-------------------------------------|-----------|-----------|-----------|
| Liquid Limit (%) = | 45 | 46 | 40 |
| Plastic Limit (%) = | 22 | 23 | 20 |
| Plasticity Index (%) = | 23 | 23 | 20 |
| Moisture Content (%) = | 28 | 22 | 22 |
| Estimated Permeability (cm./sec.) = | 10^{-7} | 10^{-7} | 10^{-7} |

Classification of Sample [& Group Symbol]: SILTY CLAY, a trace of sand

Figure: 9




U.S. BUREAU OF SOILS CLASSIFICATION

| | | | | | | | |
|--------|------|--------|--------|------|---------|------|------|
| GRAVEL | | SAND | | | | SILT | CLAY |
| COARSE | FINE | COARSE | MEDIUM | FINE | V. FINE | | |

UNIFIED SOIL CLASSIFICATION

| | | | | | |
|--------|------|--------|--------|------|-------------|
| GRAVEL | | SAND | | | SILT & CLAY |
| COARSE | FINE | COARSE | MEDIUM | FINE | |






U.S. BUREAU OF SOILS CLASSIFICATION

| | | | | | | | | | |
|--------|--|------|--|--------|--------|------|---------|------|------|
| GRAVEL | | | | SAND | | | | SILT | CLAY |
| COARSE | | FINE | | COARSE | MEDIUM | FINE | V. FINE | | |

UNIFIED SOIL CLASSIFICATION

| | | | | | | | | | |
|--------|------|--|--------|--------|------|--|--|-------------|--|
| GRAVEL | | | SAND | | | | | SILT & CLAY | |
| COARSE | FINE | | COARSE | MEDIUM | FINE | | | | |



Project: Proposed School Block
 Location: Shinning Hill Phase 3
 306 St. John's Sideroad, Town of Aurora
 Borehole No: 202 205
 Sample No: 8 5B
 Depth (m): 6.3 3.4
 Elevation (m): 265.0 270.7

| | BH./Sa. | 202/8 | 205/5B |
|-------------------------------------|---------|------------------|------------------|
| Liquid Limit (%) = | | - | - |
| Plastic Limit (%) = | | - | - |
| Plasticity Index (%) = | | - | - |
| Moisture Content (%) = | | 18 | 19 |
| Estimated Permeability (cm./sec.) = | | 10 ⁻⁴ | 10 ⁻⁵ |

Classification of Sample [& Group Symbol]: SILT, a trace of clay, a trace to some sand

Figure: 8




U.S. BUREAU OF SOILS CLASSIFICATION

| | | | | | | | |
|--------|------|--------|--------|------|---------|------|------|
| GRAVEL | | SAND | | | | SILT | CLAY |
| COARSE | FINE | COARSE | MEDIUM | FINE | V. FINE | | |

UNIFIED SOIL CLASSIFICATION

| | | | | | |
|--------|------|--------|--------|------|-------------|
| GRAVEL | | SAND | | | SILT & CLAY |
| COARSE | FINE | COARSE | MEDIUM | FINE | |



Project: Proposed School Block

Location: Shinning Hill Phase 3
306 St. John's Sideroad, Town of Aurora

Borehole No: 201

Sample No: 6

Depth (m): 3.3

Elevation (m): 268.6

Liquid Limit (%) = -

Plastic Limit (%) = -

Plasticity Index (%) = -

Moisture Content (%) = 15

Estimated Permeability

(cm./sec.) = 10^{-3}

Classification of Sample [& Group Symbol]: SANDY SILT, a trace of clay

Figure: 9

APPENDIX E

Water Level Measurements

Table E-1 - Water Level Depths and Elevations
Hydrogeological Investigation
Shining Hill (Phase 3), 162 St. John's Sideroad West, Aurora, Ontario

| Monitoring Well ID | Ground Surface Elevation (masl) | Screen Interval (masl) | 29-Sep-20 | | 16-Nov-20 | | 24-Nov-20 | | 01-Dec-20 | | 19-Jan-21 | |
|--------------------|---------------------------------|------------------------|--------------|------------------|--------------|------------------|--------------|------------------|--------------|------------------|--------------|------------------|
| | | | Depth (mbgs) | Elevation (masl) | Depth (mbgs) | Elevation (masl) | Depth (mbgs) | Elevation (masl) | Depth (mbgs) | Elevation (masl) | Depth (mbgs) | Elevation (masl) |
| BH101 | 265.00 | 257.4 to 258.9 | 4.50 | 260.50 | 4.13 | 260.87 | 4.19 | 260.81 | 3.89 | 261.11 | 3.20 | 261.80 |
| BH102 | 264.90 | 258.8 to 260.3 | 2.80 | 262.10 | 2.66 | 262.24 | 2.67 | 262.24 | 2.48 | 262.42 | 1.97 | 262.93 |
| BH103 | 268.00 | 263.4 to 265.0 | 2.50 | 265.50 | 2.40 | 265.61 | 2.40 | 265.61 | 2.26 | 265.75 | 1.82 | 266.18 |
| BH104 | 267.30 | 261.2 to 262.7 | 2.70 | 264.60 | 2.24 | 265.06 | 2.24 | 265.06 | 2.18 | 265.12 | 1.33 | 265.97 |
| BH105 | 266.80 | 250.0 to 253.1 | 7.20 | 259.60 | 6.78 | 260.02 | 6.72 | 260.08 | 6.60 | 260.20 | 6.06 | 260.74 |
| BH106 | 265.30 | 257.7 to 259.2 | DRY | DRY | 6.92 | 258.38 | 5.92 | 259.38 | 3.69 | 261.61 | 2.24 | 263.07 |
| BH107 | 262.50 | 256.4 to 257.9 | 4.20 | 258.30 | 3.56 | 258.94 | 3.61 | 258.89 | 2.82 | 259.68 | 2.24 | 260.26 |
| BH108 | 269.30 | 264.7 to 266.3 | 3.20 | 266.10 | 3.08 | 266.22 | 3.10 | 266.20 | 2.97 | 266.34 | 2.25 | 267.05 |
| BH202 | 271.30 | 265.2 to 266.7 | 4.60 | 266.70 | 4.69 | 266.61 | 4.70 | 266.61 | 4.64 | 266.67 | 4.35 | 266.95 |
| BH205 | 274.10 | 268.0 to 269.5 | 3.80 | 270.30 | 3.97 | 270.13 | 4.00 | 270.10 | 3.78 | 270.33 | 3.38 | 270.72 |
| BH206-D | 273.30 | 261.1 to 262.6 | 2.00 | 271.30 | 1.83 | 271.48 | 1.84 | 271.47 | 1.73 | 271.57 | 1.62 | 271.68 |
| BH206-S | 273.30 | 265.7 to 267.2 | 3.90 | 269.40 | 3.92 | 269.38 | 3.92 | 269.38 | 3.89 | 269.42 | 3.57 | 269.73 |
| P1 | 259.43 | - | | | DRY | DRY | 1.11 | 258.32 | 0.68 | 258.75 | 0.22 | 259.21 |
| SG1 | 258.70 | - | | | -0.27 | 258.97 | -0.27 | 258.97 | -0.29 | 258.99 | -0.26 | 258.96 |

Notes:

1. mbgs = metres below ground surface
2. masl = metres above sea level
3. Monitoring wells 101 to 108, 202, 205 and 206D/S were installed by Soil Engineers Ltd. in September 2020. The elevations provided are understood to be referenced to a geodetic datum.
4. D = deep, S = shallow
5. P = piezometer, SG = staff gauge; installed by Golder Associates Ltd. on November 16, 2020.
6. Elevation data for ground surface at the location of the P1 and SG1 were surveyed by Golder Associates Ltd. and are referenced to a geodetic datum.
7. Groundwater level data from September 29, 2020, were measured by Soil Engineers Ltd.
8. Stabilized groundwater conditions may not have been present at BH106 on Sept. 29, Nov. 16, Nov. 24, and Dec. 1, 2020.

Figure E-2: BH102 Hydrograph
Shining Hill (Phase 3), 162 St. John's Sideroad West, Aurora, Ontario




Figure E-3: BH107 Hydrograph
Shining Hill (Phase 3), 162 St. John's Sideroad West, Aurora, Ontario




Figure E-4: BH206-D Hydrograph
Shining Hill (Phase 3), 162 St. John's Sideroad West, Aurora, Ontario






Figure E-5: BH206-S Hydrograph
Shining Hill (Phase 3), 162 St. John's Sideroad West, Aurora, Ontario



APPENDIX F

Hydraulic Conductivity Testing



WELL TEST ANALYSIS

Data Set: C:\Users\JGopaul\Desktop\Shining Hill\Analysis\RHTs\BH101 (logger).aqt
 Date: 03/04/21 Time: 16:10:21

PROJECT INFORMATION

Company: Golder Associates Ltd.
 Project: 20360612
 Test Well: BH101
 Test Date: December 1, 2020

AQUIFER DATA


Saturated Thickness: 3.71 m Anisotropy Ratio (Kz/Kr): 1.

WELL DATA (BH101)

Initial Displacement: 1.12 m Static Water Column Height: 3.71 m
 Total Well Penetration Depth: 3.7 m Screen Length: 2.1 m
 Casing Radius: 0.025 m Well Radius: 0.08 m

SOLUTION

Aquifer Model: Unconfined Solution Method: Bower-Rice
 K = 2.165E-6 cm/sec $y_0 =$ 1.081 m



WELL TEST ANALYSIS

Data Set: C:\Users\JGopaul\Desktop\Shining Hill\Analysis\RHTs\BH103.aqt
 Date: 03/04/21 Time: 17:39:03

PROJECT INFORMATION

Company: Golder Associates Ltd.
 Project: 20360612
 Test Well: BH103
 Test Date: November 16, 2020

AQUIFER DATA


Saturated Thickness: 2.21 m Anisotropy Ratio (Kz/Kr): 1.

WELL DATA (BH103)

Initial Displacement: 1.04 m Static Water Column Height: 2.21 m
 Total Well Penetration Depth: 2.16 m Screen Length: 2.16 m
 Casing Radius: 0.047 m Well Radius: 0.08 m

SOLUTION

Aquifer Model: Unconfined Solution Method: Bower-Rice
 K = 0.0011 cm/sec y0 = 0.9682 m



WELL TEST ANALYSIS

Data Set: C:\Users\JGopaul\Desktop\Shining Hill\Analysis\RHTs\BH108.aqt
 Date: 03/04/21 Time: 16:39:23

PROJECT INFORMATION

Company: Golder Associates Ltd.
 Project: 20360612
 Test Well: BH108
 Test Date: November 16, 2020

AQUIFER DATA


Saturated Thickness: 1.52 m Anisotropy Ratio (Kz/Kr): 1.

WELL DATA (BH108)

Initial Displacement: 1.02 m Static Water Column Height: 1.52 m
 Total Well Penetration Depth: 1.52 m Screen Length: 1.52 m
 Casing Radius: 0.05 m Well Radius: 0.08 m

SOLUTION

Aquifer Model: Unconfined Solution Method: Bouwer-Rice
 K = 0.0004911 cm/sec y0 = 0.8149 m



WELL TEST ANALYSIS

Data Set: C:\Users\JGopaul\Desktop\Shining Hill\Analysis\RHTs\BH202.aqt
 Date: 03/04/21 Time: 17:03:42

PROJECT INFORMATION

Company: Golder Associates Ltd.
 Project: 20360612
 Test Well: BH202
 Test Date: November 16, 2020

AQUIFER DATA


Saturated Thickness: 1.91 m Anisotropy Ratio (Kz/Kr): 1.

WELL DATA (BH202)

Initial Displacement: 1.02 m Static Water Column Height: 1.91 m
 Total Well Penetration Depth: 1.41 m Screen Length: 1.41 m
 Casing Radius: 0.05 m Well Radius: 0.08 m

SOLUTION

Aquifer Model: Unconfined Solution Method: Bower-Rice
 K = 0.0003809 cm/sec y0 = 1.068 m



WELL TEST ANALYSIS

Data Set: C:\Users\JGopaul\Desktop\Shining Hill\Analysis\RHTs\BH206-S (logger).aqt
 Date: 03/04/21 Time: 17:15:18

PROJECT INFORMATION

Company: Golder Associates Ltd.
 Project: 20360612
 Test Well: BH206-S
 Test Date: December 1, 2020

AQUIFER DATA

Saturated Thickness: 3.72 m Anisotropy Ratio (Kz/Kr): 1.

WELL DATA (BH206-S)

Initial Displacement: 1.11 m Static Water Column Height: 3.72 m
 Total Well Penetration Depth: 3.72 m Screen Length: 2.1 m
 Casing Radius: 0.025 m Well Radius: 0.08 m


SOLUTION

Aquifer Model: Unconfined Solution Method: Bouwer-Rice
 K = 3.498E-6 cm/sec y0 = 1.046 m

Constant Head Permeameter Test Report - Test GP-101

Approximate Location: 30 m southwest of BH-101
 Test Depth: 1.0 mbgs

Figure F-1



| Elapsed Time (min) | Water Level in Reservoir (cm) | Water Level Change (cm) | Infiltration (cm/min) |
|--------------------|-------------------------------|-------------------------|-----------------------|
| 0.0 | 2.5 | - | - |
| 0.5 | 6.5 | 4.0 | 8.0 |
| 1.0 | 6.5 | 0.0 | 0.0 |
| 1.5 | 6.5 | 0.0 | 0.0 |
| 2.0 | 6.5 | 0.0 | 0.0 |
| 3.0 | 6.5 | 0.0 | 0.0 |
| 4.0 | 6.5 | 0.0 | 0.0 |
| 5.0 | 6.5 | 0.0 | 0.0 |
| 6.0 | 9.0 | 2.5 | 2.5 |
| 8.0 | 12.0 | 3.0 | 1.5 |
| 10.0 | 15.3 | 3.3 | 1.7 |
| 12.0 | 19.7 | 4.4 | 2.2 |
| 13.0 | 20.5 | 0.8 | 0.8 |
| 14.0 | 22.1 | 1.6 | 1.6 |
| 15.0 | 24.0 | 1.9 | 1.9 |
| 16.0 | 25.6 | 1.6 | 1.6 |
| 17.0 | 27.5 | 1.9 | 1.9 |
| 18.0 | 29.2 | 1.7 | 1.7 |
| 19.0 | 31.0 | 1.8 | 1.8 |
| 20.0 | 32.8 | 1.8 | 1.8 |
| 21.0 | 34.6 | 1.8 | 1.8 |

**Soil Type 3 - Inferred
SILTY SAND (FILL)**

Interpreted Rate of:

Water Level Change (R_1) = 3.0E-02 cm/s

Steady Intake Water Rate (Q_1) = 6.5E-02 cm³/s

hole radius (a) = 3 cm

Water column height in hole (H_1) = 7.5 cm

Shape factor for $H_1/a = (C_1) = 1.06$ -

Soil Type Coefficient $\alpha^* = 0.12$ cm⁻¹

Single Head Analysis

$$K_{fs} = \frac{C_1 Q_1}{2\pi H_1^2 + \pi \alpha^2 C_1 + 2\pi \frac{H_1}{\alpha^*}}$$

Field Saturated Hydraulic Conductivity (K_{fs})

$K_{fs} = 9E-05$ cm/s

 =input data

DATE: 2020-11-24
 PROJECT: 20360612




PREPARED BY: AGB
 REVIEW: CMK

Constant Head Permeameter Test Report - Test GP-102

Figure F-2

Approximate Location: 1 m north of BH-102
 Test Depth: 0.7 mbgs



| Elapsed Time (min) | Water Level in Reservoir (cm) | Water Level Change (cm) | Infiltration (cm/min) |
|--------------------|-------------------------------|-------------------------|-----------------------|
| 0.0 | 3.0 | - | - |
| 0.5 | 7.4 | 4.4 | 8.8 |
| 6.0 | 7.4 | 0.0 | 0.0 |
| 7.0 | 10.5 | 3.1 | 3.1 |
| 8.0 | 10.5 | 0.0 | 0.0 |
| 9.0 | 29.5 | 19.0 | 19.0 |
| 12.0 | 29.8 | 0.3 | 0.1 |
| 14.0 | 30.3 | 0.5 | 0.3 |
| 16.0 | 31.1 | 0.8 | 0.4 |
| 18.0 | 31.8 | 0.7 | 0.4 |
| 20.0 | 32.5 | 0.7 | 0.4 |
| 22.0 | 33.2 | 0.7 | 0.4 |

Soil Type 3 - SILT

Interpreted Rate of:

Water Level Change (R_1) = 6.0E-03 cm/s
 Steady Intake Water Rate (Q_1) = 1.3E-02 cm³/s
 hole radius (a) = 3 cm
 Water column height in hole (H_1) = 14 cm
 Shape factor for H_1/a (C_1) = 1.60 -
 Soil Type Coefficient α^* = 0.12 cm⁻¹

Single Head Analysis

$$K_{fs} = \frac{C_1 Q_1}{2\pi H_1^2 + \pi a^2 C_1 + 2\pi \frac{H_1}{\alpha^*}}$$

Field Saturated Hydraulic Conductivity (K_{fs})

$K_{fs} = 1E-05$ cm/s

 =input data

DATE: 2020-11-24
 PROJECT: 20360612




PREPARED BY: AGB
 REVIEW: CMK

Constant Head Permeameter Test Report - Test GP-105

Figure F-3

Approximate Location: 2 m north of BH-105
 Test Depth: 0.8 mbgs



| Elapsed Time (min) | Water Level in Reservoir (cm) | Water Level Change (cm) | Infiltration (cm/min) |
|--------------------|-------------------------------|-------------------------|-----------------------|
| 0.0 | 3.2 | - | - |
| 0.25 | 5.0 | 1.8 | 7.2 |
| 0.5 | 5.1 | 0.1 | 0.4 |
| 0.75 | 5.2 | 0.1 | 0.4 |
| 1.0 | 5.3 | 0.1 | 0.4 |
| 1.25 | 5.3 | 0.0 | 0.0 |
| 1.5 | 5.3 | 0.0 | 0.0 |
| 2.0 | 5.4 | 0.1 | 0.2 |
| 3.0 | 5.5 | 0.1 | 0.1 |
| 4.0 | 5.6 | 0.1 | 0.1 |
| 5.0 | 5.7 | 0.1 | 0.1 |
| 6.0 | 5.8 | 0.1 | 0.1 |
| 7.0 | 5.9 | 0.1 | 0.1 |
| 8.0 | 6.0 | 0.1 | 0.1 |
| 9.0 | 6.1 | 0.1 | 0.1 |
| 10.0 | 6.2 | 0.1 | 0.1 |

Soil Type 3 - SAND

Interpreted Rate of:

Water Level Change (R_1) = 1.7E-03 cm/s

Steady Intake Water Rate (Q_1) = 5.9E-02 cm³/s

hole radius (a) = 3 cm

Water column height in hole (H_1) = 5 cm

Shape factor for $H_1/a = (C_1) = 0.80$ -

Soil Type Coefficient $\alpha^* = 0.12$ cm⁻¹

Single Head Analysis

$$K_{fs} = \frac{C_1 Q_1}{2\pi H_1^2 + \pi \alpha^2 C_1 + 2\pi \frac{H_1}{\alpha^*}}$$

Field Saturated Hydraulic Conductivity (K_{fs})

$K_{fs} = 1E-04$ cm/s

 =input data

DATE: 2020-11-24
 PROJECT: 20360612




PREPARED BY: AGB
 REVIEW: CMK

Constant Head Permeameter Test Report - Test GP-106

Figure F-4

Approximate Location: 1 m north of BH-106
 Test Depth: 1.1 mbgs



| Elapsed Time (min) | Water Level in Reservoir (cm) | Water Level Change (cm) | Infiltration (cm/min) |
|--------------------|-------------------------------|-------------------------|-----------------------|
| 0.0 | 1.3 | - | - |
| 0.5 | 3.0 | 1.8 | 3.5 |
| 1.0 | 3.0 | 0.0 | 0.0 |
| 1.5 | 3.0 | 0.0 | 0.0 |
| 2.0 | 3.0 | 0.0 | 0.0 |
| 3.0 | 3.0 | 0.0 | 0.0 |
| 4.0 | 3.0 | 0.0 | 0.0 |
| 5.0 | 3.0 | 0.0 | 0.0 |
| 6.0 | 3.0 | 0.0 | 0.0 |
| 8.0 | 3.0 | 0.0 | 0.0 |
| 10.0 | 3.0 | 0.0 | 0.0 |
| 23.0 | 10.0 | 7.0 | 0.5 |
| 24.0 | 26.3 | 16.3 | 16.3 |
| 25.0 | 31.5 | 5.2 | 5.2 |
| 26.0 | 45.5 | 14.0 | 14.0 |
| 27.0 | 58.0 | 12.5 | 12.5 |
| 28.0 | 70.0 | 12.0 | 12.0 |
| 28.5 | 76.0 | 6.0 | 12.0 |

**Soil Type 3 - Inferred
SILTY FINE SAND**

Interpreted Rate of:

Water Level Change (R_1) = 2.0E-01 cm/s
 Steady Intake Water Rate (Q_1) = 4.4E-01 cm³/s
 hole radius (a) = 3 cm
 Water column height in hole (H_1) = 19 cm
 Shape factor for H_1/a (C_1) = 1.92 -
 Soil Type Coefficient α^* = 0.12 cm⁻¹

Single Head Analysis

$$K_{fs} = \frac{C_1 Q_1}{2\pi H_1^2 + \pi a^2 C_1 + 2\pi \frac{H_1}{\alpha^*}}$$

Field Saturated Hydraulic Conductivity (K_{fs})

$K_{fs} = 3E-04$ cm/s

 =input data

DATE: 2020-11-24
 PROJECT: 20360612




PREPARED BY: AGB
 REVIEW: CMK

Constant Head Permeameter Test Report - Test GP-206

Figure F-5

Approximate Location: 2.5 m south of BH-206
 Test Depth: 0.7 mbgs



| Elapsed Time (min) | Water Level in Reservoir (cm) | Water Level Change (cm) | Infiltration (cm/min) |
|--------------------|-------------------------------|-------------------------|-----------------------|
| 0.0 | 1.9 | - | - |
| 0.25 | 7.0 | 5.1 | 20.4 |
| 0.5 | 7.5 | 0.5 | 2.0 |
| 0.75 | 7.8 | 0.3 | 1.2 |
| 1.0 | 7.8 | 0.0 | 0.0 |
| 1.25 | 7.8 | 0.0 | 0.0 |
| 1.5 | 7.8 | 0.0 | 0.0 |
| 2.0 | 8.2 | 0.4 | 0.8 |
| 2.5 | 8.6 | 0.4 | 0.8 |
| 3.0 | 9.0 | 0.4 | 0.8 |
| 3.5 | 9.5 | 0.5 | 1.0 |
| 4.0 | 10.0 | 0.5 | 1.0 |
| 4.5 | 10.4 | 0.4 | 0.8 |
| 5.0 | 10.8 | 0.4 | 0.8 |
| 5.5 | 11.3 | 0.5 | 1.0 |
| 6.0 | 11.6 | 0.3 | 0.6 |
| 6.5 | 12.1 | 0.5 | 1.0 |
| 7.0 | 12.5 | 0.4 | 0.8 |
| 7.5 | 13.0 | 0.5 | 1.0 |
| 8.0 | 13.5 | 0.5 | 1.0 |
| 8.5 | 14.0 | 0.5 | 1.0 |
| 9.0 | 14.5 | 0.5 | 1.0 |

Soil Type 3 - SAND

Interpreted Rate of:

Water Level Change (R_1) = 1.7E-02 cm/s
 Steady Intake Water Rate (Q_1) = 5.9E-01 cm³/s
 hole radius (a) = 3 cm
 Water column height in hole (H_1) = 5 cm
 Shape factor for H_1/a (C_1) = 0.80 -
 Soil Type Coefficient α^* = 0.12 cm⁻¹

Single Head Analysis

$$K_{fs} = \frac{C_1 Q_1}{2\pi H_1^2 + \pi a^2 C_1 + 2\pi \frac{H_1}{\alpha^*}}$$

Field Saturated Hydraulic Conductivity (K_{fs})

$K_{fs} = 1E-03$ cm/s

 =input data

DATE: 2020-11-24
 PROJECT: 20360612



PREPARED BY: AGB
 REVIEW: CMK

APPENDIX G

Water Balance Results

**Table G-1
Meteorological Data**

Buttonville A Water Budget Means for the period 1986-2017 6158409

| Water Holding Capacity | | 125 | mm | | | | | | | | |
|-------------------------------|--------------------|----------------------|-------------|-------------|---|--|----------------|----------------|-------------|-------------|--------------------------------------|
| Heat Index | | 39.55 | | | | | | | | | |
| Lower Zone | | 75 | mm | | | | | | | | |
| A | | 1.122 | | | | | | | | | |
| Date Range | | 1986 | 2017 | | | | | | | | |
| Date | Temperature | Precipitation | Rain | Melt | Potential Evapo- transpiration | Actual Evapo- transpiration | Deficit | Surplus | Snow | Soil | Accumulated Precipitation |
| | (°C) | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| January | -5.8 | 60 | 26 | 19 | 2 | 2 | 0 | 38 | 27 | 124 | 272 |
| February | -5.6 | 51 | 20 | 24 | 1 | 1 | 0 | 42 | 33 | 125 | 323 |
| March | -0.4 | 55 | 36 | 49 | 10 | 10 | 0 | 75 | 4 | 125 | 378 |
| April | 6.7 | 75 | 71 | 7 | 34 | 34 | 0 | 45 | 0 | 124 | 453 |
| May | 13.4 | 80 | 80 | 0 | 80 | 80 | 0 | 15 | 0 | 110 | 534 |
| June | 18.7 | 90 | 90 | 0 | 116 | 116 | 0 | 8 | 0 | 76 | 622 |
| July | 21.3 | 82 | 82 | 0 | 136 | 118 | -18 | 0 | 0 | 40 | 705 |
| August | 20.3 | 77 | 77 | 0 | 120 | 87 | -33 | 4 | 0 | 27 | 777 |
| September | 16.0 | 83 | 83 | 0 | 80 | 68 | -12 | 7 | 0 | 35 | 855 |
| October | 9.2 | 73 | 73 | 0 | 40 | 38 | -2 | 7 | 0 | 63 | 73 |
| November | 3.2 | 74 | 68 | 5 | 13 | 13 | 0 | 20 | 0 | 103 | 148 |
| December | -2.6 | 64 | 37 | 15 | 3 | 3 | 0 | 32 | 12 | 119 | 211 |
| Average | 7.8 | | | | | | | | | | |
| Total | | 864 | 743 | 119 | 635 | 570 | -65 | 293 | | | |

**Table G-1
Meteorological Data**

| Water Holding Capacity | | 250 | mm | | | | | | | | | |
|-------------------------------|--------------------|----------------------|-------------|-------------|---|--|----------------|----------------|-------------|-------------|--------------------------------------|--|
| Heat Index | | 39.55 | | | | | | | | | | |
| Lower Zone | | 150 | mm | | | | | | | | | |
| A | | 1.122 | | | | | | | | | | |
| Date Range | | 1986 | 2017 | | | | | | | | | |
| Date | Temperature | Precipitation | Rain | Melt | Potential Evapo- transpiration | Actual Evapo- transpiration | Deficit | Surplus | Snow | Soil | Accumulated Precipitation | |
| | (°C) | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | |
| January | -5.8 | 60 | 26 | 19 | 2 | 2 | 0 | 22 | 27 | 236 | 272 | |
| February | -5.6 | 51 | 20 | 24 | 1 | 1 | 0 | 34 | 33 | 244 | 323 | |
| March | -0.4 | 55 | 36 | 49 | 10 | 10 | 0 | 69 | 4 | 250 | 378 | |
| April | 6.7 | 75 | 71 | 7 | 34 | 34 | 0 | 45 | 0 | 249 | 453 | |
| May | 13.4 | 80 | 80 | 0 | 80 | 80 | 0 | 15 | 0 | 235 | 534 | |
| June | 18.7 | 90 | 90 | 0 | 116 | 116 | 0 | 8 | 0 | 201 | 622 | |
| July | 21.3 | 82 | 82 | 0 | 136 | 135 | -2 | 0 | 0 | 148 | 705 | |
| August | 20.3 | 77 | 77 | 0 | 120 | 109 | -11 | 4 | 0 | 113 | 777 | |
| September | 16.0 | 83 | 83 | 0 | 80 | 73 | -7 | 7 | 0 | 116 | 855 | |
| October | 9.2 | 73 | 73 | 0 | 40 | 38 | -2 | 6 | 0 | 144 | 73 | |
| November | 3.2 | 74 | 68 | 5 | 13 | 13 | 0 | 11 | 0 | 193 | 148 | |
| December | -2.6 | 64 | 37 | 15 | 3 | 3 | 0 | 26 | 12 | 216 | 211 | |
| Average Total | 7.8 | 864 | 743 | 119 | 635 | 614 | -22 | 247 | | | | |

**Table G-1
Meteorological Data**

| Water Holding Capacity | | 400 | mm | | | | | | | | | |
|-------------------------------|--------------------|----------------------|-------------|-------------|---|--|----------------|----------------|-------------|-------------|--------------------------------------|--|
| Heat Index | | 39.55 | | | | | | | | | | |
| Lower Zone | | 240 | mm | | | | | | | | | |
| A | | 1.122 | | | | | | | | | | |
| Date Range | | 1986 | 2017 | | | | | | | | | |
| Date | Temperature | Precipitation | Rain | Melt | Potential Evapo- transpiration | Actual Evapo- transpiration | Deficit | Surplus | Snow | Soil | Accumulated Precipitation | |
| | (°C) | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | |
| January | -5.8 | 60 | 26 | 19 | 2 | 2 | 0 | 21 | 27 | 371 | 272 | |
| February | -5.6 | 51 | 20 | 24 | 1 | 1 | 0 | 28 | 33 | 385 | 323 | |
| March | -0.4 | 55 | 36 | 49 | 10 | 10 | 0 | 62 | 4 | 398 | 378 | |
| April | 6.7 | 75 | 71 | 7 | 34 | 34 | 0 | 44 | 0 | 399 | 453 | |
| May | 13.4 | 80 | 80 | 0 | 80 | 80 | 0 | 15 | 0 | 384 | 534 | |
| June | 18.7 | 90 | 90 | 0 | 116 | 116 | 0 | 8 | 0 | 350 | 622 | |
| July | 21.3 | 82 | 82 | 0 | 136 | 136 | 0 | 0 | 0 | 296 | 705 | |
| August | 20.3 | 77 | 77 | 0 | 120 | 118 | -2 | 3 | 0 | 252 | 777 | |
| September | 16.0 | 83 | 83 | 0 | 80 | 77 | -3 | 7 | 0 | 251 | 855 | |
| October | 9.2 | 73 | 73 | 0 | 40 | 39 | -1 | 6 | 0 | 279 | 73 | |
| November | 3.2 | 74 | 68 | 5 | 13 | 13 | 0 | 10 | 0 | 328 | 148 | |
| December | -2.6 | 64 | 37 | 15 | 3 | 3 | 0 | 24 | 12 | 353 | 211 | |
| Average Total | 7.8 | 864 | 743 | 119 | 635 | 629 | -6 | 228 | | | | |

**Table G-2
Annual Infiltration Rates**

PRE-DEVELOPMENT SCENARIO

| Type | WHC | Type of Land Use | Soil Type | Infiltration Factor (%) | | | |
|--|--------------|---------------------|------------|-------------------------|-------|-------|-------|
| | | | | Topo | Soils | Cover | Total |
| Residential & Recreational Buildings | 90% Precip | Buildings | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Private Property - Residence | 90% Precip | Buildings | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Private Property - Driveways / Concrete Structures | 90% Precip | Paved / Structure | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Private Property - Lawns | 125 mm | Urban Lawns | Silt Loam | 0.1 | 0.3 | 0.1 | 0.50 |
| Grassed - Lawns | 125 mm | Urban Lawns | Silt Loam | 0.15 | 0.3 | 0.1 | 0.55 |
| Asphalt Roads & Concrete Structures | 90% Precip | Paved / Structure | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Gravel Pathways | 90% Precip | Gravel | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Mineral Meadow | 250 mm | Pastures and Shrubs | Silt Loam | 0.15 | 0.3 | 0.1 | 0.55 |
| Thicket / Forest / Hedgerows / Plantations | 400 mm | Mature Forest | Silt Loam | 0.15 | 0.3 | 0.2 | 0.65 |
| Mineral Marsh | Precip - PET | Pond | Silt Loam | 0.0 | 0.0 | 0.0 | 0.00 |

POST-DEVELOPMENT SCENARIO

| Type | WHC | Type of Material | Soil Type | Infiltration Factor (%) | | | |
|--|------------|---------------------|------------|-------------------------|-------|-------|-------|
| | | | | Topo | Soils | Cover | Total |
| Residential Lawns | 125 mm | Urban Lawns | Silt Loam | 0.15 | 0.3 | 0.1 | 0.55 |
| Neighbourhood Park | 125 mm | Urban Lawns | Silt Loam | 0.20 | 0.3 | 0.1 | 0.60 |
| Neighbourhood Park - Recreational Amenities / Walkways | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Mineral Meadow | 250 mm | Pastures and Shrubs | Silt Loam | 0.15 | 0.3 | 0.1 | 0.55 |
| Forest / Hedgerows | 400 mm | Mature Forest | Silt Loam | 0.15 | 0.3 | 0.2 | 0.65 |
| Roads, Sidewalks, Parking & Paths | 90% Precip | Paved | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Single Detached - Roofs | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Single Detached - Driveways | 90% Precip | Paved | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Mid / High Rise Residential | 90% Precip | Buildings | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Mid / High Rise Residential - Lawns | 125 mm | Urban Lawns | Silt Loam | 0.1 | 0.3 | 0.1 | 0.50 |
| Private Property - School | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Private Property - Driveways / Concrete Structures | 90% Precip | Paved / Structure | Impervious | 0.0 | 0.0 | 0.0 | 0.00 |
| Private Property - Lawns | 125 mm | Urban Lawns | Silt Loam | 0.1 | 0.3 | 0.1 | 0.50 |

**Table G-2
Annual Infiltration Rates**

POST-DEVELOPMENT MITIGATION SCENARIO

| Type | WHC | Type of Material | Soil Type | Infiltration Factor (%) | | | |
|--|------------|---------------------|------------|-------------------------|-------|-------|-------|
| | | | | Topo | Soils | Cover | Total |
| Residential Lawns | 125 mm | Urban Lawns | Silt Loam | 0.15 | 0.3 | 0.1 | 0.55 |
| Neighbourhood Park - Lawn | 125 mm | Urban Lawns | Silt Loam | 0.20 | 0.3 | 0.1 | 0.60 |
| Neighbourhood Park - Recreational Amenities / Walkways | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Mineral Meadow | 250 mm | Pastures and Shrubs | Silt Loam | 0.15 | 0.3 | 0.1 | 0.55 |
| Forest / Hedgerows | 400 mm | Mature Forest | Silt Loam | 0.15 | 0.3 | 0.2 | 0.65 |
| Roads, Sidewalks, Parking & Paths | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Single Detached - Roofs | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Single Detached - Roofs (to Catchbasin Filtration Trench) | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Single Detached - Driveways / Roadways (to Catchbasin Filtration Trench) | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Single Detached - Roofs (to Rear Yard Infiltration Trench) | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.80 |
| Single Detached - Roofs (to Catchbasin Infiltration Trench - 9.2 mm) | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.57 |
| Single Detached - Driveways / Roads (to Catchbasin Infiltration Trench - 9.2 mm) | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.57 |
| Roadways (to Catchbasin Infiltration Trench- 27.3 mm) | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.81 |
| Single Detached - Roofs (to Bioswale - 29.2 mm) | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.81 |
| Single Detached - Driveways / Laneway (to Bioswale - 29.2 mm) | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.81 |
| Roadways (to Bioswale - 33.3 mm) | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.82 |
| Roadways (to Bioswale - 26.7 mm) | 90% Precip | Paved | Impervious | 0.00 | 0.0 | 0.0 | 0.81 |
| Mid / High Rise Residential | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Mid / High Rise Residential - Lawns | 125 mm | Urban Lawns | Silt Loam | 0.10 | 0.3 | 0.1 | 0.50 |
| Private Property - School | 90% Precip | Buildings | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Private Property - Driveways / Concrete Structures | 90% Precip | Paved / Structure | Impervious | 0.00 | 0.0 | 0.0 | 0.00 |
| Private Property - Lawns | 125 mm | Urban Lawns | Silt Loam | 0.1 | 0.3 | 0.1 | 0.50 |

Notes:

WHC - Water Holding Capacity

The infiltration factor is estimated by summing a factor for topography, soils and cover

Table 1: Pre-development Scenario Water Balance Results

| Catchment | Area (m ²) | Precipitation | Evapo- transpiration | Surplus | Infiltration | Runoff |
|--|------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| | | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) |
| Residential & Recreational Buildings | 4,560 | (864) 3,940 | (86) 395 | (778) 3,545 | (0) 0 | (778) 3,545 |
| Private Property - Residence | 1,168 | (864) 1,010 | (86) 100 | (778) 910 | (0) 0 | (778) 910 |
| Private Property - Driveways / Concrete Structures | 5,158 | (864) 4,455 | (86) 445 | (778) 4,010 | (0) 0 | (778) 4,010 |
| Private Property - Lawns | 28,669 | (864) 24,770 | (570) 16,340 | (293) 8,400 | (147) 4,200 | (147) 4,200 |
| Grassed - Lawns | 23,362 | (864) 20,185 | (570) 13,315 | (293) 6,845 | (161) 3,765 | (132) 3,080 |
| Asphalt Roads & Concrete Structures | 9,756 | (864) 8,430 | (86) 845 | (778) 7,585 | (0) 0 | (778) 7,585 |
| Gravel Pathways | 1,074 | (864) 925 | (86) 95 | (778) 835 | (0) 0 | (778) 835 |
| Mineral Meadow | 41,415 | (864) 35,785 | (614) 25,430 | (247) 10,230 | (136) 5,625 | (111) 4,605 |
| Thicket / Forest / Hedgerows / Plantations | 23,761 | (864) 20,530 | (629) 14,945 | (228) 5,420 | (148) 3,520 | (80) 1,900 |
| Mineral Marsh | 2,078 | (864) 1,795 | (635) 1,320 | (229) 475 | (0) 0 | (229) 475 |
| Total | 141,000 | 121,825 | 73,230 | 48,255 | 17,110 | 31,145 |

Table 2: Proposed Development Scenario Water Balance Results - Without Mitigation

| Catchment | Area | Precipitation | Evapo- transpiration | Surplus | Infiltration | Runoff |
|--|-------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| | (m ²) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) |
| Residential Lawns | 24,649 | (864) 21,300 | (570) 14,050 | (293) 7,220 | (161) 3,970 | (132) 3,250 |
| Neighbourhood Park | 2,415 | (864) 2,085 | (570) 1,375 | (293) 710 | (176) 425 | (117) 285 |
| Neighbourhood Park - Recreational Amenities / Walkways | 13,685 | (864) 11,825 | (86) 1,185 | (778) 10,640 | (0) 0 | (778) 10,640 |
| Mineral Meadow | 1,338 | (864) 1,155 | (614) 820 | (247) 330 | (136) 180 | (111) 150 |
| Forest / Hedgerows | 6,567 | (864) 5,675 | (629) 4,130 | (228) 1,500 | (148) 975 | (80) 525 |
| Single Detached - Roofs | 21,827 | (864) 18,860 | (86) 1,890 | (778) 16,970 | (0) 0 | (778) 16,970 |
| Single Detached - Driveways | 7,242 | (864) 6,255 | (86) 625 | (778) 5,630 | (0) 0 | (778) 5,630 |
| Mid / High Rise Residential | 6,960 | (864) 6,015 | (86) 600 | (778) 5,410 | (0) 0 | (778) 5,410 |
| Mid / High Rise Residential - Lawns | 1,740 | (864) 1,505 | (570) 995 | (293) 510 | (147) 255 | (147) 255 |
| Private Property - School | 1,168 | (864) 1,010 | (86) 100 | (778) 910 | (0) 0 | (778) 910 |
| Private Property - Driveways / Concrete Structures | 5,158 | (864) 4,455 | (86) 445 | (778) 4,010 | (0) 0 | (778) 4,010 |
| Private Property - Lawns | 28,669 | (864) 24,770 | (570) 16,340 | (293) 8,400 | (147) 4,200 | (147) 4,200 |
| Roads, Sidewalks, Parking & Paths | 19,582 | (864) 16,920 | (86) 1,690 | (778) 15,225 | (0) 0 | (778) 15,225 |
| Total | 141,000 | 121,830 | 44,245 | 77,465 | 10,005 | 67,460 |

Table 3: Proposed Development Scenario Water Balance Results - With Mitigation

| Catchment | Area | Precipitation | Evapo- transpiration | Surplus | Infiltration | Runoff |
|--|-------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| | (m ²) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) | (mm/yr) (m ³ /yr) |
| Residential Lawns | 24,649 | (864) 21,295 | (570) 14,050 | (293) 7,220 | (161) 3,970 | (132) 3,250 |
| Neighbourhood Park - Lawn | 2,415 | (864) 2,085 | (570) 1,375 | (293) 710 | (176) 425 | (117) 285 |
| Neighbourhood Park - Recreational Amenities / Walkways | 13,685 | (864) 11,825 | (86) 1,185 | (778) 10,640 | (0) 0 | (778) 10,640 |
| Mineral Meadow | 1,338 | (864) 1,155 | (614) 820 | (247) 330 | (136) 180 | (111) 150 |
| Forest / Hedgerows | 6,567 | (864) 5,675 | (629) 4,130 | (228) 1,495 | (148) 975 | (80) 520 |
| Single Detached - Roofs | 1,376 | (864) 1,190 | (86) 120 | (778) 1,070 | (0) 0 | (778) 1,070 |
| Single Detached - Roofs (to Catchbasin Filtration Trench) | 11,163 | (864) 9,645 | (86) 965 | (778) 8,680 | (0) 0 | (778) 8,680 |
| Single Detached - Driveways / Roadways (to Catchbasin Filtration Trench) | 14,391 | (864) 12,435 | (86) 1,245 | (778) 11,190 | (0) 0 | (778) 11,190 |
| Single Detached - Roofs (to Rear Yard Infiltration Trench) | 5,656 | (864) 4,885 | (86) 490 | (778) 4,400 | (622) 3,520 | (156) 880 |
| Single Detached - Roofs (to Catchbasin Infiltration Trench - 9.2 mm) | 2,547 | (864) 2,200 | (86) 220 | (778) 1,980 | (443) 1,130 | (334) 850 |
| Single Detached - Driveways / Roads (to Catchbasin Infiltration Trench - 9.2 mm) | 5,138 | (864) 4,440 | (86) 445 | (778) 3,995 | (443) 2,275 | (334) 1,720 |
| Roadways (to Catchbasin Infiltration Trench- 27.3 mm) | 1,060 | (864) 915 | (86) 90 | (778) 825 | (630) 670 | (148) 155 |
| Single Detached - Roofs (to Bioswale - 29.2 mm) | 1,084 | (864) 940 | (86) 95 | (778) 845 | (630) 680 | (148) 165 |
| Single Detached - Driveways / Laneway (to Bioswale - 29.2 mm) | 2,123 | (864) 1,835 | (86) 180 | (778) 1,650 | (630) 1,335 | (148) 315 |
| Roadways (to Bioswale - 33.3 mm) | 1,060 | (864) 915 | (86) 90 | (778) 825 | (638) 675 | (140) 150 |
| Roadways (to Bioswale - 26.7 mm) | 552 | (864) 475 | (86) 50 | (778) 430 | (630) 350 | (148) 80 |
| Mid / High Rise Residential | 6,960 | (864) 6,015 | (86) 600 | (778) 5,410 | (0) 0 | (778) 5,410 |
| Mid / High Rise Residential - Lawns | 1,740 | (864) 1,505 | (570) 995 | (293) 510 | (147) 255 | (147) 255 |
| Private Property - School | 1,168 | (864) 1,010 | (86) 100 | (778) 910 | (0) 0 | (778) 910 |
| Private Property - Driveways / Concrete Structures | 5,158 | (864) 4,455 | (86) 445 | (778) 4,010 | (0) 0 | (778) 4,010 |
| Private Property - Lawns | 28,669 | (864) 24,770 | (570) 16,340 | (293) 8,400 | (147) 4,200 | (147) 4,200 |
| Roads, Sidewalks, Parking & Paths | 2,500 | (864) 2,160 | (86) 215 | (778) 1,945 | (0) 0 | (778) 1,945 |
| Total | 141,000 | 121,825 | 44,245 | 77,470 | 20,640 | 56,830 |



golder.com